

Datos técnicos

Fluke TL175-HV CAT III 1500 V TwistGuard™ Test Leads



Características principales

- TwistGuard™ technology features an adjustable tip that enhances safety during use.
- Heavy-duty leads tested for 30,000+ bends
- Rated CAT III 1500 V, CAT IV 1000 V for high voltage safety standards
- See compatible products below

Descripción general del producto: Fluke TL175-HV CAT III 1500 V TwistGuard™ Test Leads

The Fluke TL175-HV CAT III 1500 V TwistGuard™ Test Leads are ideal for high voltage testing in solar and industrial applications, meeting CAT III 1500 V and CAT IV 1000 V safety standards.

- High Voltage Testing: Specifically designed for applications requiring higher voltage testing and measurement, such as solar photovoltaic (PV) systems and industrial environments.
- Safety Compliance: Meets CAT III 1500 V and CAT IV 1000 V safety standards, ensuring reliable and safe operation in demanding conditions.
- TwistGuard™ Technology: Innovative extendable tip guard enhances safety by allowing adjustable tip length, minimizing risks like arc flash during measurements.
- Durable Construction: Built with double layers of flexible silicone insulation, maintaining flexibility and preventing



- cracking even in cold weather.
- **Robust Performance:** Tested to withstand over 30,000 bends without failure, ensuring long-lasting reliability in rigorous environments.
 - **Compatibility:** Equipped with shrouded 4 mm banana plugs, compatible with a wide range of digital multimeters and measurement instruments.
 - **Ergonomic Design:** Designed for comfortable handling and reduced user fatigue during prolonged testing sessions, enhancing overall efficiency.

Especificaciones: Fluke TL175-HV CAT III 1500 V TwistGuard™ Test Leads

Specifications	
Safety Ratings	IEC 61010-031, CAT II 1500 V, CAT III 1500 V, CAT IV 1000 V
Current Measurement	10 A maximum
Insulation	Double insulated silicone wire
Lead Length	1.5 meters (5 feet)
Environmental Ratings	-20°C to 55°C (-4°F to 131°F), 90% Relative Humidity, Altitude 2000 m (6,562 ft), Pollution Degree 2

Fluke. *Manteniendo su mundo en marcha.*

Fluke Corporation
Everett, WA 98206 EE.UU.

Para obtener información adicional En EE. UU.
(800) 443-5853

En Europa/Medio Oriente/África
+31 (0)40 267 5100

En Canadá (800)-36-FLUKE
www.fluke.com

Latin America
Tel: +1 (425) 446-5500
www.fluke.com/laam

©2025 Fluke Corporation. Reservados todos los derechos. Impreso en los Países Bajos. Información sujeta a modificación sin previo aviso.
10/2025

No está permitido modificar este documento sin autorización por escrito de Fluke Corporation.