



PowerFlex 755TS

[20G21ND8P0JA0NNNNN](#)



Representative Rendering, Not The Actual Product

PowerFlex 755TS AC Drive, with dual Embedded EtherNet/IP, Standard Protection, Forced Air, AC Input with Precharge Terminals, Open Type, 480 VAC, 3 PH, 8 Amps, (Fr1 5HP ND, 3HP HD/Fr2 5HP ND, 5HP HD), CM Jumper Installed, DB (No HIM), Frame 2

Product Details

BASE DRIVE CONFIGURATION	
Bulletin Number	PowerFlex 755TS AC Drive, with dual Embedded EtherNet/IP
Corrosive Gas Protection and Cooling Type	Standard Protection, Forced Air
Voltage Class	480 VAC, 3 PH
Output Current	8 Amps, (Fr1 5HP ND, 3HP HD/Fr2 5HP ND, 5HP HD)
Enclosure	Open Type
Frame Size	Frame 2
Input Type	AC Input with Precharge, Includes DC Terminals
Filtering & CM Cap Config	CM Jumper Installed
Dynamic Braking	DB Transistor
HIM	Blank (No HIM)

Supporting Documentation and Downloads

- [Photo](#)
- [Circuit Protection Design and SCCR Tables](#)