



Fuse-link, high speed, 315 A, AC 690 V, 200 kA, DIN 000, 21 x 40 x 100 mm, aR, DIN, IEC



Referencia **FUSE 315A 690V 000U/80 AR UC**
 Catalog No. **170M1322**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	315
Rated voltage			AC 690 V
Construction size			DIN 000
Size			21 x 40 x 100 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with offset bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

Technical data ETIM 7.0

Aparatos de protección y fusibles (EG000020) / Fusible para baja tensión tipo NH (EC000055)			
Tecnología electrónica, de automatización y de mando de procesos / Instalación eléctricas, equipo / Inserto de fusibles / Inserto de fusibles de baja tensión (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Tamaño de construcción			Otros
Corriente nominal		Ampere	315
Tensión nominal		Volt	690
Tipo de tensión			CA
Capacidad de conmutación nominal/poder de corte		kiloamper	200
Categoría de uso			aR (protección suplementaria de semiconductores)
Tipo de indicador de estado de fusible			Ninguno

Additional product information (links)

High-speed full-line catalogue (pdf)	http://www1.cooperbusssmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf
--------------------------------------	---