THIS C	COPY IS F	PROVID	ED ON	A RESTRICTED BASIS AND IS NOT TO BE US	ED IN ANY WAY DETRIMENTAL TO	THE INTE	RESTS OF PAN	NDUIT CORP.			
Mc	aterial			High Conductivity Seamless Copper Tube							
Pla	Iting			Electro-Tin							
Wir	re Size			6 AWG				DIA			
Wir	re Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric				27±.02			coded narkings
Wir	re Strip L	_ength	١	1-1/8 in.	.48±.04	AJAW CU					
Stu	ıd Size			1/4 in.	.48±.04 ₹	ל ≝ ייייל			PAN BLUE DIE		
	Listed W Innecto			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		50±.02	1	13 REF.	-		
	Temper ting	rature		90° C	-	63±.0	2				
	C.S.A Certified Wire Connector			Yes			2.49	9±.06 ——			
	nduit Co Barrel	olor C	ode	BLUE							
	nduit Di Barrel	e Inde	ex No.	P24					— 1.07±.04 —	Ве	veled wire entry
Die	Alternate Industry Die Index No. () on Barrel			(7)	Wire inst	pection	window		1.07 ±.04		
		CI	SP ERTIFIEI	 B LISTED Wire Connector 	.08±.01	1 1				(22±.01	.31±.01
										• TINLEY PARK,	ILLINOIS
									LCC6-14JA	NW-L	
00	9/04	<u>ЈНИ</u> Ц		RELEASED			SCALE	-		Long Barrel wi	
REV	DATE	BY	СНК	DESCRIPTIO	DN	ECN	N/A			LCC6-14.	IAW-CUST