



# Product: <u>5302FE</u> ☑

Security & Sound, #18-4c, BC, Shielded, CMR

# **Product Description**

Security & Sound Cable, Riser-CMR, 4-18 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

# **Technical Specifications**

### Product Overview

Construction Details     Conductor     Element   Number of Element   Size   Stranding   Material     Conductor(s)   4   18 AWG   7x26   BC - Bare Copper     Insulation   Element   Material   Nom. Thickness   Nom. Insulation Diameter   Color Code     Conductor(s)   PO - Polyolefin   0.009 in (0.23 mm)   0.062 in (1.6 mm)   Black, Red, White, Green						
Conductor(s)     4     Ta AWG     7x26     BC - Bare Copper       Insulation     Image: Conductor(s)     Material     Nom. Thickness     Nom. Insulation Diameter     Color Code       Conductor(s)     PO - Polyolefin     0.009 in (0.23 mm)     0.062 in (1.6 mm)     Black, Red, White, Green	Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment					
Element   Number of Element   Size   Stranding   Material     Conductor(s)   4   18 AWG   7x26   BC - Bare Copper     Insulation   Image: Stranding	Construction Details					
Conductor(s)     4     Table     7x26     BC - Bare Copper       Insulation     Image: Conductor(s)     Material     Nom. Thickness     Nom. Insulation Diameter     Color Code       Conductor(s)     PO - Polyolefin     0.009 in (0.23 mm)     0.062 in (1.6 mm)     Black, Red, White, Green	Conductor					
Insulation     Material     Nom. Thickness     Nom. Insulation Diameter     Color Code       Conductor(s)     PO - Polyolefin     0.009 in (0.23 mm)     0.062 in (1.6 mm)     Black, Red, White, Green						
ElementMaterialNom. ThicknessNom. Insulation DiameterColor CodeConductor(s)PO - Polyolefin0.009 in (0.23 mm)0.062 in (1.6 mm)Black, Red, White, Green						
Outer Shield						
	Outer Shield					
Shield Type Material Coverage Drainwire Type						
Tape Bi-Laminate (Alum+Poly) 100% 24 AWG (7x32) TC						
Outer Jacket						
Material Nom. Thickness Nom. Diameter Ripcord						
PVC - Polyvinyl Chloride     0.017 in (0.43 mm)     0.188 in (4.78 mm)     Yes						
Overall Cable Diameter (Nominal): 0.188 in (4.78 mm)						

# **Electrical Characteristics**

#### Electricals

	Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
	Conductor(s)	6.5 Ohm/1000ft	27 pF/ft (89 pF/m)	48.5 pF/ft (159 pF/m)	4 Amps per conductor @ 25°C

#### Voltage

UL Voltage Rating 300 V (CMR)

# **Mechanical Characteristics**

#### Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

### Bend Radius

Stationary Min.	Installation Min.		
1.9 in (48 mm)	1.9 in (48 mm)		

Max. Pull Tension:	104 lbs (47.2 kg)
Bulk Cable Weight:	31 lbs/1000ft

### Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor		
Flammability / Reaction to Fire:	UL 1666 Riser, FT4, IEC 60332-1-2		
CPR Compliance:	CPR Euroclass: Eca		
NEC / UL Compliance:	Article 800, CMR		
CEC / C(UL) Compliance:	CMG		
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)		
APAC Compliance:	China RoHS II (GB/T 26572-2011)		
Plenum Number:	6302FE		

### **History**

Update and Revision:

Revision Number: 0.408 Revision Date: 06-30-2022

#### **Part Numbers**

#### Variants

ltem #	Color	Putup Type	Length	UPC/EAN
5302FE.00152	Chrome	Reel	152 m	8719605008220
5302FE.00305	Chrome	Reel	305 m	8719605008237
5302FE.00U305	Chrome	Reel	305 m	8719605008244
5302FE 0081000	Gray			612825336846
5302FE 008500	Gray			612825159551
5302FE 008C250	Gray			
5302FE 008U1000	Gray			612825159537
5302FE 008U500	Gray			612825159544

#### © 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.