



Product: 6120UL ☑

Fire Alarm, #14-2c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 2-14 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Fire Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Conductor(s)	2	14 AWG	Solid	BC - Bare Copper

Insulation

Element	Material	Nom. Thickness	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	0.010 in (0.25 mm)	Black, Red

Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.015 in (0.38 mm)	0.201 in (5.11 mm)	Yes
Overall Cable Diameter (N	Nominal): 0.201 in (5.11 mm)	

Electrical Characteristics

Electricals

	Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
I	Conductor(s)	2.43 Ohm/1000ft (7.97 Ohm/km)	37 pF/ft (120 pF/m)	8.0 Amps per conductor @ 25°C

Voltage

UL Voltage Rating
300 V (FPLP)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum)
NEC / UL Compliance:	Article 760, FPLP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	California State Fire Marshall
Non-Plenum Number:	5120UL

History

Update and Revision:	Revision Number: 0.286 Revision Date: 12-15-2021

Variants

Item #	Color	UPC
6120UL 0101000	Black	612825173731
6120UL D151000	Blue	612825173700
6120UL 0011000	Brown	612825173717
6120UL 0051000	Green	612825350354
6120UL 8771000	Natural	612825350385
6120UL 0031000	Orange	612825350347
6120UL 0021000	Red	612825339564
6120UL 002500	Red	612825173724
6120UL 0071000	Violet	612825350361
6120UL 0071000	Violet	612825350361
6120UL 0041000	Yellow	612825352228

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

6120UL 0021000 6120UL 0101000 6120UL 002500 6120UL 0011000 6120UL D151000 6120UL 0041000 6120UL 002A1000 6120UL 8771000 6120UL 0051000 6120UL 0031000 6120UL 0071000 6120UL 0091000