



Product Description

High Performance Instrumentation, 1 Pair 20AWG (19x32) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC-ER

Technical Specifications

Product Overview

FIGUUCI	Overview					
Suitable A	pplications:	Instru	mentation, S	ensors, Valves, Positio	ners, 4-2	0mA, 0-10
Constru	ction Details					
oonstru	letion Details					
Conductor						
Element	Number of Element	Size	Stranding	Material		
Pair(s)	1	20 AWG	19x32	TC - Tinned Copper		
Insulation						
Element	Material	Nor	n. Thickness	Nom. Insulation Di	amotor	Color Co
Pair(s)	PVC - Polyvinyl Chlo					Black, Re
(0)				, 0.012 (1.0)		Diaon, Ho
Outer Shie	ld					
Shield Ty	pe Material		Coverage	Drainwire Type		
Таре	Bi-Laminate (Alu	m+Poly)	100% 2	2 AWG (19x34) TC		
Outer Jack	(et					
М	aterial Nom	n. Thickne	ss Nom.	Diameter		
PVC - Pol	yvinyl Chloride 0.037	7 in (0.94 n	nm) 0.221 ir	(5.61 mm)		
Overall Ca	able Diameter (Nomin	al): 0.221	in (5.61 mm)			
oronali ot		0.221				
Electric	al Characteristi	cs				
Electricals						

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Shield	Max. Current
Pair(s)	11.3 Ohm/1000ft	52 pF/ft (170 pF/m)	97 pF/ft (320 pF/m)	3.8 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 300 V (PLTC, CMG)

Mechanical Characteristics

Temperature	
UL Temperature	Operating
105°C	-30°C to +105°C
Table Notes:	

Bend Radius

Stationary Min. Installation Min.

2.2 in (56 mm) 2.2 in (56 mm)	
Max. Pull Tension:	54 lbs (24 kg)
Bulk Cable Weight:	29 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance
Flammability / Reaction to Fire:	UL 1685 UL Loading, FT4, T-29-520, IEEE 1202
NEC / UL Compliance:	Article 725, Article 727, Article 800, CMG, ITC-ER, PLTC-ER
AWM Compliance:	AWM 2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision: Revision Number: 0.501 Revision Date: 06-30-2022

Part Numbers

Variants

ltem #	Color	UPC
9320 0605000	Chrome	612825228936
9320 060U1000	Chrome	612825228912
9320 060U500	Chrome	612825228929

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.