

- COMPATIBLE WITH ALL HD-CVI, HD-TVI, HD-AHD
- NO POWER REQUIRED
- 60dB CROSS TALK AND NOISE IMMUNITY
- COMPACT SIZE AND EASY INSTALLATION
- BUILT-IN TRANSIENT SUPPRESSION PROTECTION
- INDICATED LED LIGHTS

The BE8016HDP Balun Power-Video signals are routed via UTP and RJ45. The unit is a passive (non-amplified) device that allows the transmission of real-time monochrome or color video over Unshielded Twisted-Pair (UTP) telephone wire.

1ch PASSIVE HD-CVI / TVI / AHD VIDEO BALUN

VIDEO FORMAT	HD-CVI/TVI/AD, NTS, and Pal
FREQUENCY RESPONSE	DC to 60MHz
ATTENUATION	0.5dB
CMRR	60dB
	PAL/NTSC
SYNC. SYSTEM	Internal Sync
SENSOR AREA	4.8mmx3.6mm
VIDEO OUTPUT	1.0Vp~p75Ω
S/N RATIO	More than 50dB (AGC OFF)
IMPEDANCE	Coax, Male BNC 75ohms RJ45 100ohms

DISTANCE

720p CVI	Up to 450m
720p AHD	Up to 320m
1080p CVI	Up to 250m
720p/1080p TVI	Up to 200m

WORKING ENVIRONMENT

WORKING TEMPERATURE	-10°C to +50°C
STORAGE TEMPERATURE	-30°C to +70°C
HUMIDITY	0 to 95%



Up to 450m
Up to 320m
Up to 250m