

Bolide BN7009H

Datasheet



BN7009H H.265

4MP High Definition Wide Angle IR
Dome Camera



HIGHLIGHTS

- 2.8mm Wide Angle Lens
- Compression H.265 / H.264
- Built-In POE
- IR Distance up to 75 ft.
- IP66
- BNC Output
- Two-Way (Audio In-Out)

The new iPac NX series features up to 4 Mega Pixels of stunning Ultra HD resolution combined with the Next Generation of compression standards - High Efficiency Video Coding (HEVC / H.265)- which allows for bitrates nearly half those of other cameras utilizing older H.264 compression technology. The iPac NX series offers double the storage and half of the bandwidth requirements without sacrificing resolution or frame rate.

MECHANICAL SPECIFICATIONS	
Image Sensor	1/3" Progressive Scan CMOS
Minimum Illumination	0.01Lux @(F1.2,AGC ON), 0.02Lux @(F1.2,AGC OFF), 0 Lux with IR
Shutter Speed	1/5 s – 1/20,000 s
Lens Type	2.8mm
Lens Mount	M12
Day and Night	IR Cut Filter with Auto Switch
Dynamic Range	Wide Dynamic Range
Digital Noise Reduction	2D / 3D DNR
COMPRESSION	
Video Compression	H.265 / H.264 / MJPEG
Image Resolution	Upto 4MP (2592 X 1520)
Video Bit Rate	256K-8M
IMAGE	
Frame Rate	4MP (2592 X 1520) @ 20fps, 3MP (2048 x 1536) @ 30fps, 1080P (1920 x 1080) @ 30fps, 720P (1280 x 720) @ 30fps - 960H (1280 x 960), Substream @ 30 fps, D1 (704 x 480) - VGA (640 x 480) - QVGA (320 x 240) @30 fps, Mobilestream @ 10 fps, QVGA (320 X 240) - @1-30 fps
Image Settings	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, and adjustable browser
Day and Night Switch	Auto / Schedule / Triggered by Alarm In
INTERFACE	
System Compatibility	ONVIF 2.4, RTSP
Interface	1 RJ45 10M / 100M Ethernet Interface
IR Distance	IR Upto 75 .
POE	Built-In POE
Edge Recording	Micro SD slot
Security	Flash-Prevention, Dual Stream, Heartbeat, Mirror, Password Protection, PrivacyMask, IP Address Filtering
ELECTRICAL	
Power Supply	12 VDC ± 10%, POE (802.3af)
Power Consumption	Max. 5 W (Max. 7W with IR cut filter on)
Operating Temp.	-22 °F - 140 °F Humidity 95% or less (non-condensing)
PHYSICAL	
Net Weight	1 lb
Weather-Rating	IP66 Rated and IK10