

# **LifeSafety Power Kits**

## LifeSafety Regulated Power Supply Kits - Mercury Hardware

Ordering LifeSafety Power kits is as simple as 1-2-3. Just answer a few questions to get started. The first two questions in each group have been answered for you. Scroll down to see all 4 groups.

- 1. Using Mercury or HID hardware Answer: Mercury Hardware
- 2. Do you require lock power Answer: No Lock Power Included
- 3. How many doors are you looking to secure Choose door capacity (2, 4, 8, or 16 doors) below

| М |  |  |  |
|---|--|--|--|
|   |  |  |  |
|   |  |  |  |

### Description

## AC-LSP-2DR-MER



Two Door Mercury Single Voltage Integrated Power System supporting two AC-MER-CONT-1DR or one AC-MER-CONT-2DR (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet (unless using two AC-MER-CONT-1DR). Cabinet size: 12" x 14" x 4.5" with door lock, tamper switch and two (2) keys. Weight 14 lb.

### AC-LSP-4DR-MER



Four Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with one AC-MER-CON-MR52 (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 16" x 20" x 4.5" with door lock, tamper switch and two (2) keys. Weight 19 lb.

# AC-LSP-8DR-MER



Eight Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with three AC-MER-CON-MR52 (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 4.5" with door lock, tamper switch and two (2) keys. Weight 25 lb.

## AC-LSP-16DR-MER



Sixteen Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with Seven AC-MER-CON-MR52 (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 150 watt 12V/12A or 24V/6A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 4.5" with door lock, tamper switch and two (2) keys. Weight 25 lb.

All prices are exclusive of taxes and freight. Avigilon reserves the right to make changes to pricing and discount margins. All installation and use of Avigilon software is governed by its end user license agreement (EULA). Contact Avigilon or visit www.avigilon.com to get a copy of the EULA.

CONFIDENTIAL: The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Avigilon Corporation. © 2017 Avigilon. AVIGILON, the AVIGILON logo, TRUSTED SECURITY SOLUTIONS, AVIGILON CONTROL CENTER, and ACC are trademarks of Avigilon Corporation. Other marks referred to herein are the property of their respective owners.

Page 15 of 70