

TWO-DOOR WITH 3-POINT LATCHES AND FLOOR STANDS TYPE 4



These enclosures are ideal for indoor or outdoor applications where it is necessary to protect controls and instrumentation from wet, non-corrosive environments. The design features HOFFMAN's exclusive PowerGlide Handle with 3-point latching for secure closure and floor stands that provide additional height and access for cleaning under the enclosure.

FEATURES & BENEFITS

Three-point latch for security and ease of use

Return flange around the door opening excludes liquids and contaminants

Removable centerpost permits easy panel installation

3-point latch system with PowerGlide padlocking handles

Seams continuously welded and ground smooth; no holes or knockouts

Body stiffeners

Panel supports

Heavy gauge continuous hinge with stainless steel hinge pin

Data pocket is high-impact thermoplastic

12-in. floor stands are welded to enclosure

Heavy-duty lifting eyes

Oil-resistant door gasket

Collar stud for mounting optional panels

Grounding stud on body

Bonding provision on door

Provision for mounting fluorescent light

SPECIFICATIONS

Color Gray

Color Code ANSI 61

Finish Powder Coated

Thickness 12 ga

Table 1/2

Catalog Number	Height	Width	Depth	Protection Rating	Material	Panel
A62H4810LP3PT	62.06 in	48.06 in	10.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A60P48
A62H4818LP3PT	62.06 in	48.06 in	18.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A60P48
A62H6012LP3PT	62.06 in	60.06 in	12.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A60P60
A62H6018LP3PT	62.06 in	60.06 in	18.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A60P60
A74H6012LP3PT	74.06 in	60.06 in	12.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A72P60
A74H6018LP3PT	74.06 in	60.06 in	18.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A72P60
A74H7212LP3PT	74.06 in	72.06 in	12.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A72P72
A74H7218LP3PT	74.06 in	72.06 in	18.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A72P72
A74H7224LP3PT	74.06 in	72.06 in	24.06 in	NEMA Type 12; NEMA Type 13; NEMA Type 4; NEMA Type 3; IP66	Mild Steel	A72P72

Table 2/2

Catalog Number	Conductive Panel	Body Stiffener	Panel Size
A62H4810LP3PT	A60P48G	15 in	56.00 x 44.00 in
A62H4818LP3PT	A60P48G	15 in	56.00 x 44.00 in
A62H6012LP3PT	A60P60G	21 in	56.00 x 56.00 in
A62H6018LP3PT	A60P60G	21 in	56.00 x 56.00 in
A74H6012LP3PT	A72P60G	21 in	68.00 x 56.00 in
A74H6018LP3PT	A72P60G	21 in	68.00 x 56.00 in
A74H7212LP3PT	A72P72G	24 in	68.00 x 68.00 in
A74H7218LP3PT	A72P72G	24 in	68.00 x 68.00 in
A74H7224LP3PT	A72P72G	24 in	68.00 x 68.00 in

Order panel separately.

2100 Hoffman Way
Anoka, MN 55303-1745 | USA
763.421.2240



Our powerful portfolio of brands:
[nVent.com](https://www.nVent.com) **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.