

## FIBERGLASS FREE-STAND TYPE 4X



An economical housing for corrosive environments, single-door, free-stand enclosures provide a versatile solution for applications that require flexibility when mounting panels and racks. Benefits include easy access to equipment, larger capacity for control systems, steel reinforcements for stability and strength, captivated door screws and an optional PowerGlide Handle for secure latching.

### FEATURES & BENEFITS

Fiberglass-reinforced polyester material has excellent temperature and chemical resistance and exhibits outstanding physical properties

Fiberglass material is easily punched, drilled, filed or sawed

Models have either a 3-point latching system with handle or stainless steel captivated door screws

Seamless foam-in-place gasket assures water-tight and dust-tight seal

Painted steel top, bottom and side internal reinforcements standard; stainless steel corner reinforcements optional

Heavy-duty Type 316 stainless steel lifting eyes

Accessory mounting channels attached horizontally to interior body sides at top, bottom and center; painted mounting channels standard; stainless steel optional

Panels and rack-mounting angles can be mounted anywhere along corner channels; panels can be mounted on sides or back

Hinges are corrosion-resistant fiberglass with Type 316 stainless steel hinge pins

Large, high-impact thermoplastic data pocket (12.00 x 12.00 in. or 305 x 305 mm) is

Molded-in angular sealing flange directs water away from gasket area

Type 316 stainless steel PowerGlide Handle on handle versions

Material is halogen free

Optional mild-steel panels are painted white

Optional conductive panels are unpainted

### SPECIFICATIONS

**Color** Gray

**Finish** Smooth Gloss

**Thickness** 0.22 in

Table 1/1					
Catalog Number	Height	Width	Depth	Protection Rating	Material
A722525FGFS3PT	72 in	25 in	24.5 in	NEMA Type 4; NEMA Type 4X; NEMA Type 3; NEMA Type 3R; NEMA Type 12; NEMA Type 13; IP66	Fiberglass
A722525FGFS	72 in	25 in	24.5 in	NEMA Type 4; NEMA Type 4X; NEMA Type 3; NEMA Type 3R; NEMA Type 12; NEMA Type 13; IP66	Fiberglass

For CALIFORNIA residents only - WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Please note that by posting this Proposition 65 warning, we are notifying you that one or more of the Proposition 65 listed chemicals may be present in this product. With HOFFMAN's products, the exposure to these chemicals may be of no significant risk to you, but out of caution and to ensure your well-being, we have elected to place this warning on our site to make sure our customers are informed. You can find more information at <http://www.oehha.ca.gov/proposition-65/about-proposition-65>.

2100 Hoffman Way  
Anoka, MN 55303-1745 | USA  
763.421.2240



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.