

MEDIUM DRIP-SHIELD HINGED-COVER TYPE 3R



Medium Drip-Shield Hinged-Cover, Type 3R, protects wiring and other electrical components in outdoor applications that require protection from rain, sleet, snow or dripping water. It offers the flexibility of securing enclosure with an optional padlock and collar studs for optional panel mounting. These enclosures have a size range of 16 x 12 x 6-in. to 60 x 36 x 12-in.

FEATURES & BENEFITS

Drip shield top and seam-free sides, front, and back protect from rain, snow, or sleet

16-gauge plated steel continuous hinge has stainless steel pin

Cover fastened securely with captive plated steel screws

Collar studs provided for mounting optional panels

Hasp and staple provided for padlocking

No gasketing or knockouts

Enclosures are finished with paint over plated surfaces

SPECIFICATIONS

Finish Galvanized; Powder Coated

Color Gray

Color Code ANSI 61

Table 1/3

Catalog Number	Height	Width	Depth	Protection Rating	Material	Body Thickness
A16R126HCR	406 mm	305 mm	152 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm
A16R166HCR	406 mm	406 mm	152 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm
A18R1810HCR	457 mm	457 mm	254 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm
A18R186HCR	457 mm	457 mm	152 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm
A20R166HCR	508 mm	406 mm	152 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm

Catalog Number	Height	Width	Depth	Protection Rating	Material	Body Thickness
A20R208HCR	508 mm	508 mm	203 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm
A24R208HCR	610 mm	508 mm	203 mm	NEMA Type 3R; IP32	Mild Steel	1.52 mm
A24R2410HCR	610 mm	610 mm	254 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A24R248HCR	610 mm	610 mm	203 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A30R2410HCR	762 mm	610 mm	254 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A30R248HCR	762 mm	610 mm	203 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A30R3012HCR	762 mm	762 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A30R3016HCR	762 mm	762 mm	406 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A30R308HCR	762 mm	762 mm	203 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A36R2412HCR	914 mm	610 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A36R3012HCR	914 mm	762 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A36R3610HCR	914 mm	914 mm	254 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A36R3612HCR	914 mm	914 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A42R3012HCR	1067 mm	762 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A42R3612HCR	1067 mm	914 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A48R3612HCR	1219 mm	914 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A48R3616HCR	1219 mm	914 mm	406 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm
A60R3612HCR	1524 mm	914 mm	305 mm	NEMA Type 3R; IP32	Mild Steel	1.9 mm

Table 2/3

Catalog Number	Door Thickness	Panel Size	Mounting	Panel	Perforated Panel	Aluminum Panel
A16R126HCR	1.52 mm	330 x 229 mm	432 x 76 mm	A16P12	A16P12PP	A16P12AL
A16R166HCR	1.52 mm	330 x 330 mm	432 x 330 mm	A16P16	A16P16PP	A16P16AL
A18R1810HCR	1.52 mm	381 x 381 mm	483 x 330 mm	A18P18	A18P18PP	
A18R186HCR	1.52 mm	381 x 381 mm	483 x 330 mm	A18P18	A18P18PP	
A20R166HCR	1.52 mm	432 x 330 mm	533 x 330 mm	A20P16	A20P16PP	A20P16AL
A20R208HCR	1.9 mm	432 x 432 mm	533 x 330 mm	A20P20	A20P20PP	A20P20AL
A24R208HCR	1.9 mm	533 x 432 mm	635 x 330 mm	A24P20	A24P20PP	A24P20AL
A24R2410HCR	1.9 mm	533 x 533 mm	635 x 330 mm	A24P24	A24P24PP	A24P24AL
A24R248HCR	1.9 mm	533 x 533 mm	635 x 330 mm	A24P24	A24P24PP	A24P24AL
A30R2410HCR	1.9 mm	686 x 533 mm	787 x 330 mm	A30P24	A30P24PP	A30P24AL
A30R248HCR	1.9 mm	686 x 533 mm	787 x 330 mm	A30P24	A30P24PP	A30P24AL
A30R3012HCR	1.9 mm	686 x 686 mm	787 x 686 mm	A30P30	A30P30PP	

CatalogNumber	DoorThickness	Panel Size	Mounting	Panel	PerforatedPanel	AluminumPanel
A30R3016HCR	1.9 mm	686 x 686 mm	787 x 686 mm	A30P30	A30P30PP	
A30R308HCR	1.9 mm	686 x 686 mm	787 x 686 mm	A30P30	A30P30PP	
A36R2412HCR	1.9 mm	838 x 533 mm	940 x 330 mm	A36P24	A36P24PP	A36P24AL
A36R3012HCR	1.9 mm	838 x 686 mm	940 x 686 mm	A36P30	A36P30PP	
A36R3610HCR	1.9 mm	838 x 838 mm	940 x 762 mm	A36P36	A36P36PP	
A36R3612HCR	1.9 mm	838 x 838 mm	940 x 686 mm	A36P36	A36P36PP	
A42R3012HCR	1.9 mm	991 x 686 mm	1092 x 686 mm	A42P30		
A42R3612HCR	1.9 mm	991 x 838 mm	1092 x 686 mm	A42P36		
A48R3612HCR	1.9 mm	1143 x 838 mm	1245 x 686 mm	A48P36		A48P36AL
A48R3616HCR	1.9 mm	1143 x 838 mm	1245 x 686 mm	A48P36		A48P36AL
A60R3612HCR	1.9 mm	1448 x 838 mm	1549 x 686 mm	A60P36		A60P36AL

Table 3/3

Catalog Number	Overall Length
A16R126HCR	457 mm
A16R166HCR	457 mm
A18R1810HCR	508 mm
A18R186HCR	508 mm
A20R166HCR	559 mm
A20R208HCR	559 mm
A24R208HCR	660 mm
A24R2410HCR	660 mm
A24R248HCR	660 mm
A30R2410HCR	813 mm
A30R248HCR	813 mm
A30R3012HCR	813 mm
A30R3016HCR	813 mm
A30R308HCR	813 mm
A36R2412HCR	965 mm
A36R3012HCR	965 mm
A36R3610HCR	965 mm

Catalog Number	Overall Length
A36R3612HCR	965 mm
A42R3012HCR	1118 mm
A42R3612HCR	1118 mm
A48R3612HCR	1270 mm
A48R3616HCR	1270 mm
A60R3612HCR	1575 mm

Purchase panels separately.

Panel edges are flanged when greater than 30 inches (762mm).

2100 Hoffman Way
 Anoka, MN 55303-1745 | USA
 763.421.2240



Our powerful portfolio of brands:
 nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.