

DISCONNECT ENCLOSURE WITH CLAMPS TYPE 4



For disconnect applications in which a clamp-secured door is preferred. Clamps on three sides of the door keep liquid and contaminants out. Preferred cutout accepts major brand disconnect switches and circuit breakers..

Each Disconnect Enclosure with Clamps, Type 4 is furnished with adjustable door interlock bracket fastened to door, instructions to locate and install disconnect switches, circuit breakers and operating mechanisms.

FEATURES & BENEFITS

- Seams continuously welded and ground smooth
- External mounting brackets
- External-formed flange around all sides of enclosure opening
- Stainless steel door clamps on three sides of door
- Removable door with continuous hinge
- Type 4 rated door gasket
- Collar studs for mounting optional panels
- Holes in body for mounting disconnect operating handle and operating mechanism
- Bonding provision on door
- Adjustable door interlock bracket fastened to door) and instructions for installing disconnects

SPECIFICATIONS

Protection Rating NEMA Type 4; IP66

Material Mild Steel

Color Code ANSI 61

Thickness 1.9 mm

Table 1/2

Catalog Number	Finish	Height	Color	Width	Depth	Panel Size
A24HS2108LP	Powder Coated	610 mm	Gray	543 mm	203 mm	533 x 432 mm

Catalog Number	Finish	Height	Color	Width	Depth	Panel Size
A24HS2508LP	Powder Coated	610 mm	Gray	645 mm	203 mm	533 x 533 mm
A30HS2508LP	Powder Coated	762 mm	Gray	645 mm	203 mm	686 x 533 mm
A36HS2508LP	Powder Coated	914 mm	Gray	645 mm	203 mm	838 x 533 mm
A36HS3108LP	Powder Coated	914 mm	Gray	797 mm	203 mm	838 x 686 mm
A42HS3112LP	Powder Coated	1067 mm	Gray	797 mm	305 mm	991 x 686 mm
A42HS3712LP	Powder Coated	1067 mm	Gray	949 mm	305 mm	991 x 838 mm
A48HS3712LP	Powder Coated	1219 mm	Gray	949 mm	305 mm	1143 x 838 mm
A60HS3712LP	Powder Coated	1524 mm	Gray	949 mm	305 mm	1448 x 838 mm

Table 2/2

Catalog Number	Conductive Panel	Clamp Quantity	Data Pocket Size	Panel
A24HS2108LP	A24P20G	5	152 x 152 mm	A24P20
A24HS2508LP	A24P24G	5	152 x 152 mm	A24P24
A30HS2508LP	A30P24G	5	305 x 305 mm	A30P24
A36HS2508LP	A36P24G	5	305 x 305 mm	A36P24
A36HS3108LP	A36P30G	7	305 x 305 mm	A36P30
A42HS3112LP	A42P30G	10	152 x 152 mm	A42P30
A42HS3712LP	A42P36G	10	305 x 305 mm	A42P36
A48HS3712LP	A48P36G	10	305 x 305 mm	A48P36
A60HS3712LP	A60P36G	11	305 x 305 mm	A60P36

Purchase panels separately.

NOTE: nVent HOFFMAN cannot guarantee compatibility of disconnect configurations with third-party latching.

2100 Hoffman Way
Anoka, MN 55303-1745 | USA
763.421.2240



Our powerful portfolio of brands:
[nVent.com](https://www.nVent.com) **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.