



APC Smart-UPS X-Series External Battery Pack Rack/Tower 120V, 1200VAh, rackmount, 4U

SMX120BP

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually Ships within 2 Weeks

Main

4U Number of rack unit Lead-Acid battery **Battery Type Provided Equipment** Installation guide Rack Mounting brackets

Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	7.01 in (17.8 cm)
Depth	19.02 in (48.3 cm)
Net Weight	134.28 lb(US) (60.91 kg)
Mounting Mode	Rack-mounted

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

Batteries & Runtime

Battery blocks per string	10
Device mounting	Enclosed battery cartridge
Included Battery Modules	0
Battery Slots Empty	0
RBC Quantity	2

Battery Voltage	120 V
Replacement battery	APCRBC143 ☐
	APCRBC143US ☐

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304292562
Returnability	No

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.99 in (33 cm)
Package 1 Width	23.07 in (58.6 cm)
Package 1 Length	24.92 in (63.3 cm)
Package 1 Weight	144.29 lb(US) (65.45 kg)

Offer Sustainability

<u>-</u>	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)