

Product data sheet

Specifications



Rack PDU, Basic, 1U, 30A, 120V, (10)5-20



AP9560

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage	100 V 120 V
Main Output Voltage	120 V
Input Connection Type	NEMA L5-30P
Number of rack unit	1U
Cable length	12 ft (3.66 m)
Number of cables	1
Provided Equipment	User Manual Rack Mounting brackets

Physical

Color	Black
Height	1.73 in (4.4 cm)
Width	17.60 in (44.7 cm)
Depth	2.24 in (5.7 cm)
Net Weight	5.51 lb(US) (2.5 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Line Rated Current	24 A
Acceptable Input Voltage	90...132 V
Max line current	24 A
Input current limits	30 A
Load Capacity	2880 VA
Input Frequency	50/60 Hz

Output

Number of power socket outlets 10 NEMA 5-20R

Conformance

Product Certifications cUL Listed
UL Listed

Standards UL 60950

Environmental

Ambient air temperature for operation 5...113 °F (-15...45 °C)

Relative Humidity 0...95 %

Operating altitude 0...10000 ft

Ambient Air Temperature for Storage -13...149 °F (-25...65 °C)

Storage Relative Humidity 0...95 %

Storage altitude 0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category 11309-APC RESALE PRODUCTS

Discount Schedule APC1

GTIN 731304192930

Returnability No

Country of origin IN

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 5.98 in (15.2 cm)

Package 1 Width 6.97 in (17.7 cm)

Package 1 Length 19.13 in (48.6 cm)

Package 1 Weight 8.02 lb(US) (3.64 kg)

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Lead free Yes

Optimized Energy Efficiency Energy efficient product

Take-back Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)