

TS°30 Test Set

The TS30 Test Set features a rigid test set case design, at an affordable price. The ergonomic non-slip grip handle provides improved handling of the set in all weather conditions. Includes DataSafe™ operation so technicians can clip onto a line in monitor mode, without disrupting existing data traffic.

- High impedance DataSafe operation in monitor mode
- DropSafe[™] reliability passes 20-foot drop test
- RainSafe[™] protection in severe weather conditions
- Mute switch
- Last number redial

Model	Description
30800009	TS30 test set with Angled Bed-of-Nails (ABN)
30800001	TS30 test set with piercing pin clips



TS[®]22 Series Test Sets

The TS22 Series offers a unique built-in, one-way amplified speaker that provides three audio levels for hands-free listening and use with automated voice response systems. Multiple memories enable storage of nine 18-digit telephone numbers in repertory dialer (speed dialing) for easy access to test boards, the central office and other frequently called numbers. The last number redial feature eliminates the need to re-key your last entry. The TS22 test set offers an unbeatable combination of reliability, durability and expanded utility.

- Amplified speaker for hands-free monitoring
- Two-way speakerphone for true hands-free conversation
- DropSafe[™] reliability passes 20-foot drop test
- RainSafe[™] protection in severe weather conditions
- Stores nine 18-digit numbers in repertory dialer (speed dialing)

Model	Description	
22801009	TS22A test set with Angled Bed-of-Nails (ABN)	
22801007	TS22A test set with ground start cord	
22801004	TS22A test set with 346A plug	
22801001	TS22A test set with piercing pin clips	
22800009	TS22 test set with Angled Bed-of-Nails (ABN)	
22800007	07 TS22 test set with ground start cord	
22800004	TS22 test set with 346A plug	
22800001	TS22 test set with piercing pin clips	



TS°25D LCD Test Set

intuitive, common-sense menus easy-to-read and use.

- Caller-ID and Call-waiting Caller-ID
- Amplified speakers for hands-free monitoring
- Data lockout and data lockout override
- Tone generator for wire identification
- Talk battery to power voice conversation on dry (non-powered) lines

Model	Description
25501109	TS25D test set with Angled Bed-o
25501009	TS25D test set with Angled Bed-o
25501004	TS25D test set with 346A plug
25500400	TS25D pouch only
25500300	TS25D battery door with belt clip
25500100	Earpiece, TS25D test set

TS°19 Test Set

The TS19 Test Set combines all the essential test set features at an affordable price. This test set was specifically designed for in-house telecom technicians. Its high impedance monitor prevents accidental disruption of service from clipping onto a data line while in Monitor Mode, thus ensuring the integrity of critical data lines. Features such as tone (DTMF) or pulse operation, talk/monitor capabilities, polarity test button and last number redial make this test set the perfect combination of features and price.

- High impedance DataSafe operation in monitor mode
- Tone (DTMF) and pulse operation and last number redial
- Polarity indication in talk mode

Model	Description
19800009	TS19 test set with Angled Be
19800003	TS19 test set with banana jac

The TS25D Test Set features data lockout and lockout override, making you completely safe in talk or monitor mode. The DSL/POTS filtering technology allows you to safely draw dial tone without downing DSL. A built-in analog tone generator simplifies wire identification with a probe. An amplified speaker makes monitoring the line hands-free, so you can keep working. The Talk Battery function provides voltage to carry voice conversation on non-powered pairs. Also includes Caller-ID and Call-waiting Caller-ID functions. All in a compact unit with an oversized, robust liquid crystal display (LCD) that makes the



of-Nails (ABN) kit (includes pouch and earpiece) of-Nails (ABN)

ed-of-Nails (ABN)

acks to alligator clips



Test Equipment 99 Washington Street Depot Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com