



Fuse-link, low voltage, 20 A, AC 500 V, 100 kA, D2, gL/gG, IEC, time-delay



Powering Business Worldwide™

**Referencia** FUSE-D2 20A T GL/GG 500VAC E27  
**Catalog No.** 20D27

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 500 V
Construction size			D2
Utilization category			gL/gG
Breaking Capacity		kA	100
usable for size/applications			E27 for domestic and general industrial applications
Release characteristic	class		time-delay
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

### Technical data ETIM 5.0

Circuit breakers and fuses (EG000020) / Cinta fusible Diazed (EC000099)			
Tecnología electrónica, de automatización y de mando de procesos / Instalación eléctricas, equipo / Inserto de fusibles / Inserto de fusibles D (ecl@ss8-27-14-20-04 [AFZ799011])			
Tamaño de construcción			DII
Corriente nominal		A	20
Tensión nominal		V	500
Código de color			Azul
Categoría de uso			gL/gG (protección de cable/equipo)
Tipo de disparo			Retardo de tiempo