

# Product data sheet

Specifications



## Rack PDU 2G, Switched, ZeroU, 15A, 100-120V, (8) 5-15

AP8931

### Overview

#### Presentation

APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

**Lead time** Usually in Stock

### Main

**Main Input Voltage** 100 V  
120 V

**PDU Type** Switched

**Main Output Voltage** 100 V  
120 V

**Input Connection Type** NEMA 5-15P

**Number of rack unit** 0U

**Cable length** 10 ft (3.05 m)

**Number of cables** 1

**Provided Equipment** Installation guide  
Rack Mounting brackets  
Serial configuration cable  
Safety guide

### Physical

**Color** Black

**Height** 38.90 in (98.8 cm)

**Width** 2.17 in (5.5 cm)

**Depth** 1.81 in (4.6 cm)

**Net Weight** 9.17 lb(US) (4.16 kg)

**Mounting Location** Side

**Mounting preference** No preference

**Mounting Mode** Not rack-mountable

## Input

|                          |             |
|--------------------------|-------------|
| Line Rated Current       | 12 A        |
| Acceptable Input Voltage | 100...120 V |
| Input current limits     | 15 A        |
| Load Capacity            | 1440 VA     |
| Input Frequency          | 50/60 Hz    |

## Output

|                                |              |
|--------------------------------|--------------|
| Number of power socket outlets | 8 NEMA 5-15R |
|--------------------------------|--------------|

## Conformance

|                        |   |
|------------------------|---|
| Product Certifications | cUL Listed<br>PSE<br>UL Listed                |
| Standards              | FCC Part 15 class A<br>ICES-003<br>UL 60950-1 |

## Environmental

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | 23...140 °F (-5...60 °C)         |
| Relative Humidity                     | 5...95 %                         |
| Operating altitude                    | 0...10000 ft                     |
| Ambient Air Temperature for Storage   | -13...149 °F (-25...65 °C)       |
| Storage Relative Humidity             | 5...95 %                         |
| Storage altitude                      | 0...50000 ft (0.00...15240.00 m) |

## Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304307525 |
|------|--------------|

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | Db                     |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 44.53 in (113.1 cm)    |
| Package 1 Width              | 4.26 in (10.83 cm)     |
| Package 1 Length             | 6.30 in (16 cm)        |
| Package 1 Weight             | 11.07 lb(US) (5.02 kg) |

## Offer Sustainability

|                           |  |
|---------------------------|--|
| Sustainable offer status  | Green Premium product  |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive         | Compliant<br><a href="#">EU RoHS Declaration</a>   |
| Lead free                 | Yes  |
| Mercury free              | Yes  |

---

|                                    |   |
|------------------------------------|---|
| <b>RoHS exemption information</b>  | <a href="#">Yes</a>                           |
| <b>Environmental Disclosure</b>    | <a href="#">Product Environmental Profile</a> |
| <b>Circularity Profile</b>         | <a href="#">End of Life Information</a>       |
| <b>Optimized Energy Efficiency</b> | Energy efficient product                      |
| <b>Take-back</b>                   | Take-back program available                   |

---

### **Contractual warranty**

---

|                 |                           |
|-----------------|---------------------------|
| <b>Warranty</b> | 2 years repair or replace |
|-----------------|---------------------------|

### **Recommended replacement(s)**