




# Semiconductor Fuse

## 10-30A, 500 Volts

BIF Document  
50955  
Size 6x32



**Pre-Arcing** Time-Current Characteristic Curves  
**FWH 010A6F-030A6F**

Approved: **NN**  
Rev. Date: **MAR-97**

Page **1 of 1**  
Pub. Date: **JAN-98**

**COOPER** Bussmann  
12-28-98  
SB98107 Rev. A

BUSSMANN  
P.O. Box 14460  
St. Louis, MO 63178-4460  
U.S.A.  
Phone: 314-394-2877  
Fax: 800-544-2570  
Int'l Fax: 314-527-1413

BUSSMANN U.K.  
Burton-on-the-Wolds  
Leicestershire LE12 5TH  
England  
Phone: 44-1509-882737  
Fax: 44-1509-882786

BUSSMANN  
DENMARK  
5 Literbuen  
DK-2740 Skovlunde  
Copenhagen, Denmark  
Phone: 45-4485-0900  
Fax: 45-4485-0901

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.