

TABLA DE SELECCIÓN

Series de Multímetros de Ganchos Profesionales



Medición		CL2100 TRMS 400A CA/CD c/temp.	CL2200 RMS 600A CA/CD	CL2500 TRMS 1000A CA/CD	CL3000 200A CA	CL3100 200A CA	CL3200 200A CA
	Corriente CA	400A	600A	1000A	200A	200A	200A
	Corriente CD	400A	600A	1000A	N/A	N/A	N/A
	Voltaje CA	750V	750V	750V	750V	750V	750V
	Voltaje CD	1000V	1000V	1000V	1000V	1000V	1000V
	Micro Amps	0.1 ~ 2000µA	≥0.1µA	N/A	N/A	N/A	N/A
	Resistencia	40MΩ	60MΩ	60MΩ	40MΩ	40MΩ	40MΩ
	Capacitancia	4000µF	6000µF	6000µF	40µF	N/A	N/A
	Frecuencia	499.9kHz	499.9kHz	●	100kHz	N/A	N/A
	Prueba de Diodo	●	●	●	●	N/A	N/A
	Continuidad	●	●	●	●	●	●
	Temperatura	-22°~399.9°F	N/A	N/A	N/A	N/A	N/A
	Voltaje sin Contacto	●	●	●	N/A	N/A	●

Características							
	Pantalla LCD conteo	4000	5900	6000	4000	4000	4000
	Retención de Datos	●	●	●	●	N/A	●
	Apagado Automático	●	●	●	●	N/A	●
	Luz de Fondo	●	●	●	●	●	●
	Luz de Trabajo	●	●	●	●	●	●
	Rango Manual	●	●	●	●	●	●
	Retención Máximo	●	●	N/A	N/A	●	N/A
	Retención Mínima	●	●	N/A	N/A	●	N/A
	Gráfico de Barras	●	●	●	N/A	●	●
	Soporte Magnético	●	●	●	N/A	●	●
	Lectura Relativa	●	●	●	N/A	●	N/A
	Valor Eficaz (RMS)	●	●	●	N/A	N/A	N/A

Certificación							
---------------	--	--	--	--	--	--	--

No.Cat.	Clasif.CAT	Tamaño Gancho	Altura	Ancho	Peso (oz.)	Accesorios Incluidos
CL2100	CAT III 600V	1.25" (32 mm)	8.875" (225 mm)	3.375" (86 mm)	10.7 (303 g)	Cables de prueba, pilas, estuche y termopolar
CL2200	CAT IV 600V	1.37" (34 mm)	7.65" (194 mm)	3.375" (86 mm)	11.9 (303 g)	Cables de prueba, pilas y estuche
CL2500	CAT IV 600V	1.97" (50 mm)	8.09" (205 mm)	2.56" (65 mm)	13.6 (386 g)	Cables de prueba, pilas y estuche
CL3000	CAT III 600V	0.5" (13 mm)	7.50" (191 mm)	2.70" (69 mm)	7.4 (210 g)	Cables de prueba, pilas y estuche
CL3100	CAT IV 600V	0.5" (13 mm)	10.25" (260 mm)	2.50" (64 mm)	8.6 (244 g)	Cables de prueba, pilas y estuche
CL3200	CAT IV 600V	0.63" (16 mm)	7.06" (179 mm)	2.56" (65 mm)	7.9 (224 g)	Cables de prueba, pilas y estuche