

PRODUCT-DETAILS

216MVS4WH

216MVS4WH Industrial Switched Interlocked Socket Outlet



General Information

Extended Product Type	216MVS4WH
Product ID	2CMA163256R1000
EAN	7392696632560
Catalog Description	216MVS4WH Industrial Switched Interlocked Socket Outlet
Long Description	Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 4h, rated current 16A, IP67 watertight, 2-poles+earth

Technical

Standards	IEC 60309-1, -2, -4
Function	Switched Interlocked Socket outlet, vertical, Heavy Duty
Suitable For	Switched Interlocked Socket Outlets, Vertical
Suitable for Product Class	IEC Industrial Plugs and Sockets
Rated Voltage (U_r)	100 ... 130 V
Rated Current (I_n)	16 A
Frequency (f)	50 Hz 60 Hz
Mounting Holes	79.5x79.5
Number of Poles	3
Tightening Torque	WireClamp0.8 N-m
Connection Type	Screw
Mounting Type	Vertical
Protection Type	Switched Interlocked

Type of Fastening	Inner Lying Mounting
Clock Position Of Grounding Contact	4 hour
Mounting Orientation	Vertical
Enclosure Material	Thermoplastic polyester (PBT)
Housing Material	Thermoplastic (PBT)
Material	Plastic
Additional Information	2P+E
Recommended Screw Driver	PH2
Cable Entry Position	Knock-out on Top and drill marks down
Cable Outlets Per Side	1xØ40+1xØ50 mm on top and drill marks on bottom
Model Number	Surface mounted (plaster)
RAL Number	RAL 7001 - Silver Grey
Color	Yellow
Cable Cross-Section	1.5 ... 4 mm ²

Environmental

Ambient Temperature	-25 ... 40 °C
Degree of Protection	IP67 IP69
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	2CMC000057M0000

Technical UL/CSA

Tightening Torque UL/CSA	7.1 in-lb
--------------------------	-----------

Dimensions

Product Net Width	160 mm
Product Net Height	205 mm
Product Net Depth / Length	307 mm
Product Net Weight	1.83 kg
Size	200X160X310

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	215 mm
Package Level 1 Height	165 mm
Package Level 1 Depth / Length	335 mm
Package Level 1 Gross Weight	1.83 kg
Package Level 1 EAN	7392696632560
Package Level 2 Units	pallet (lift) 42 piece
Package Level 2 Width	800 mm
Package Level 2 Height	900 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Gross Weight	96.86 kg

Package Level 2 EAN

7392696068260

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365015
E-Number (Finland)	2417132
E-Number (Norway)	2417132
E-Number (Sweden)	2417132
Country of Origin	Czech Republic (CZ)

Certificates and Declarations (Document Number)

Declaration	2CMC700005D0001
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
Instructions and Manuals	2CMC000029M0001
REACH Declaration	2CMC700005D0001
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660004X0203

Popular Downloads

Data Sheet, Technical Information	2CMC000029M0001
Installation Manual	2CMC000029M0001
Instructions and Manuals	2CMC000029M0001
Mechanical Drawings	9AKK107991A3924

Classifications

ETIM 7	EC001321 - CEE socket outlet
ETIM 8	EC001321 - CEE socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85365015
UNSPSC	39121406
eClass	27440510
IDEA Granular Category Code (IGCC)	4536 >> Electrical receptacles

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

