

PRODUCT-DETAILS

5353GR

INSUL.90 DEG LIQUIDTITE GRD FTG 3/4



General Information

Extended Product Type	5353GR
Product ID	7TAD012300R0023
EAN	5415022326604
Catalog Description	INSUL.90 DEG LIQUIDTITE GRD FTG 3/4
Long Description	3/4 Inch External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, 90 Degree Angle, With Revolver Lug, With Tin to plated Copper Alloy Lug for Awg #14 to #2 Ground Wire. for Use In Wet Locations. 10 Pieces

Additional Information

Application	To positively bond conduit to box or enclosure
Product Type	Grounding Connectors-90 degree

Ordering

EAN	5415022326604
UPC	786210900094
Customs Tariff Number	8547900010

Technical

Number of Batteries	0
Material	Malleable Iron
Size	3/4 Inch

Environmental

WEEE Category

Product Not in WEEE Scope

Container Information

Package Level 1 Units	10 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	6 in 152 mm
Package Level 1 Width	5 in 127 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000120
Instructions and Manuals	5353GR

Classifications

ETIM 8	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

