

PRODUCT-DETAILS

XT1H 160 TMD 160-1600 3p F F

XT1H 160 TMD 160-1600 3p F F



General Information

Extended Product Type	XT1H 160 TMD 160-1600 3p F F
Product ID	1SDA067454R1
EAN	8015644013486
Catalog Description	XT1H 160 TMD 160-1600 3p F F
Long Description	C.BREAKER TMAX XT1H 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 160-1600 A

Ordering

Order Code US and Canada	XT1HE3160AFF000XXX
EAN	8015644013486
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm
Product Net Weight	1.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.18 kg
Package Level 1 EAN	8015644013486

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	9AKK107991A8215 9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
SCIP	56dc0760-7ff8-4b75-9d5f-ff6578a7ed3c Italy (IT)
Toxic Substances Control Act - TSCA	9AKK108467A8326

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 15 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	160 A
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I_i)	1600 A
Rated Insulation Voltage (U_i)	800 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 75 kA (230 V AC) 75 kA (240 V AC) 75 kA (380 V AC) 52.5 kA (415 V AC) 37.5 kA (440 V AC) 32.5 kA (500 V AC) 25 kA

Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(525 V AC) 17.5 kA
	(690 V AC) 5 kA
	(250 V DC) 2 Poles in Series 52.5 kA
	(500 V DC) 3 Poles in Series 52.5 kA
	(220 V AC) 100 kA
	(230 V AC) 100 kA
	(240 V AC) 100 kA
	(380 V AC) 70 kA
	(415 V AC) 70 kA
	(440 V AC) 65 kA
	(500 V AC) 50 kA
	(525 V AC) 35 kA
(690 V AC) 10 kA	
(250 V DC) 2 Poles in Series 70 kA	
(500 V DC) 3 Poles in Series 70 kA	
Rated Uninterrupted Current (I _u)	160 A
Release	TMD
Release Type	TM
Setting Range	112...160 A
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	XT1
Terminal Connection Type	Fixed Circuit-Breakers
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Certificates and Declarations (Document Number)

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5532
Environmental Information	9AKK107991A8215 9AKK108467A6707
GL Certificate	1SDL000163R0103
Instructions and Manuals	1SDH000719R0001
LR Certificate	1SDL000163R0100
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

eClass

V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

