



## 1492-H...

## 1492-WFB4...

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Single-circuit fusible terminal block with or without fuse indication.

Single-circuit fuse block with or without fuse indication.

Certifications	UL		CSA	IEC	UL		CSA	IEC
	300V AC/DC		300V AC/DC	500V AC/DC	300V AC/DC		300V AC/DC	500V AC/DC
Voltage Rating	H6/WFB4		10...57V AC/DC		10...57V AC/DC			
	H5/WFB424		100...300V AC		85...264V AC			
	H4/WFB4250							
Maximum Current	15 A			15 A		15 A *		
Wire Range (Rated Cross Section)	#30...12 AWG		0.5...4 mm <sup>2</sup>		#30...12 AWG		0.5...4 mm <sup>2</sup>	
Wire Strip Length	0.38 in. (9.7 mm)			0.31 in. (8 mm)				
Recommended Tightening Torque	7.1 lb•in (0.8 N•m)			2.65...5.3 lb•in (0.3...0.6 N•m)				
Density	33 pcs/ft (109pcs /m)			38 pcs/ft (125 pcs/m)				
Housing Temperature Range	-40...+195 °F (-40...+90 °C)			-40...+195 °F (-40...+90 °C)				
<b>Indicator Type</b>								
H6/WFB4	Non-Indicating			Non-Indicating				
H5/WFB424	Red LED			Red LED				
H4/WFB4250	Neon			Neon				
<b>Leakage Current</b>								
H6/WFB4	—			—				
H5/WFB424	2 mA @ 24V			2 mA @ 24V				
H4/WFB4250	2 mA @ 300V			2 mA @ 300V				
Fuse Size (Not Supplied)	1/4 x 1-1/4 in.			5 x 20 mm				
Short-Circuit Current Rating	See page 12-42							

Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	
Color:	Black No-indication	<b>1492-H6</b>	25	<b>1492-WFB4</b>	50
	Black w/LED	<b>1492-H5</b>	25	<b>1492-WFB424</b>	50
	Black w/Neon	<b>1492-H4</b>	25	<b>1492-WFB4250</b>	50
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	
Mounting Rails:					
1 m Symmetrical DIN (Steel)	<b>199-DR1</b>	10	<b>199-DR1</b>	10	
1 m Symmetrical DIN (Aluminum)	<b>1492-DR5</b>	10	<b>1492-DR5</b>	10	
1 m Hi-Rise Sym. DIN (Aluminum)	<b>1492-DR6</b>	2	<b>1492-DR6</b>	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	<b>1492-DR7</b>	2	<b>1492-DR7</b>	2	
3 ft Scored A-B Rail	<b>1492-N1</b>	20	—	—	
3 ft Rigid A-B Rail	<b>1492-N22</b>	20	—	—	
3 ft High Rise A-B Rail	<b>1492-N44</b>	2	—	—	
Standoff Brackets (Use Every 12 in.)	<b>1492-N25</b>	2	—	—	
End Barrier	<b>1492-N37</b>	50	Not Required	—	
End Anchors and Retainers:					
Screwless End Retainer	<b>1492-ERL35</b>	20	<b>1492-ERL35</b>	20	
DIN Rail — Normal Duty	<b>1492-EAJ35</b>	100	<b>1492-EAJ35</b>	100	
DIN Rail — Heavy Duty	<b>1492-EAHJ35</b>	50	<b>1492-EAHJ35</b>	50	
A-B Rail — Heavy Duty	<b>1492-N23</b>	10	—	—	
10-Pole Side Jumper *	<b>1492-N49</b>	10	<b>1492-SJFB8-10</b>	10	
Side Jumper Insulating Sleeve	<b>1492-SJS</b>	10	—	—	
Other Accessories:					
Partition Plate	—	—	<b>1492-PPSL3</b>	50	
Marking Systems:					
Snap-In Marker Card — For Base Block	—	5	<b>1492-MS8X12</b> (56/card)	5	
	—	5	<b>1492-MS8X9</b> (56/card)	5	
For Handle	<b>1492-MS8X12</b> (56/card)	5	<b>1492-MS8X9</b> (56/card)	5	
	<b>1492-MS8X9</b> (56/card)	5			
Adhesive Labels	1492-ALHFB (50/sheet)	1	1492-ALHFB (50/card)	1	

\* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.

\* Cat. No. 1492-N49 is uninsulated. Cat. No. 1492-SJFB8-10 is insulated.

## IEC Terminal Block Accessories

## Jumpers

## Side Jumpers

For Use With	Pkg Qty.	Cat. No.
1492-WM4, W4	50	<b>1492-N42</b>
1492-H4, H5, H6, H7	10	<b>1492-N49</b>
	10	* <b>1492-SJS</b>
1492-W3, WR3	10	<b>1492-SJ5-10</b>
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	<b>1492-SJ5A-10</b>
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	<b>1492-SJ5A-24</b>
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	<b>1492-SJ5B-24</b>
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	<b>1492-SJ5B-10</b>
1492-WM4, W4, W4TW	10	⊛ <b>1492-SJ6-10</b>
1492-JT3M	5	<b>1492-SJ6A-50</b>
1492-W10	10	<b>1492-SJ8-10</b>
1492-JD3FB, JDG3FB	50	<b>1492-SJ8A-4</b>
1492-JD3FB, JDG3FB	50	1492-SJ8A-3
1492-JD3FB, JDG3FB	50	1492-SJ8A-2
1492-LMP3, LMP3Q, LMJ3, LM3, LM3Q, LMP3E, LMP3QE	50	<b>1492-SJLM5-2</b>
1492-WMD1	10	‡ <b>1492-SJMD5-12</b>
1492-WFB4, WFB424, WFB4250	10	<b>1492-SJFB8-10</b>
1492-WM3	10	<b>1492-SJM5-10</b>
1492-WTF3, WTS3, WTF3LP, WTS3LP, WTF3LN, WTS3LN	10	<b>1492-SJT5-20-R</b>
1492-WTF3, WTS3, WTF3LP, WTS3LP, WTF3LN, WTS3LN	10	<b>1492-SJT5-20-B</b>

Note: Side jumpers carry the same current rating as the terminal block used with it

\* Side jumper insulating sleeve only for use with Cat. No. 1492-N49

⊛ Use jumper on single side of terminal block only

‡ Uninsulated

## Two-Level Jumper

For Use With	Pkg Qty.	Cat. No.
1492-LTF3 (Connects Two Levels within a 1492-LTF3 Terminal Block)	20	<b>1492-CJL5D</b>