# **Product data sheet**

Specifications





# RACK PDU, BASIC, HALF HEIGHT, 100-240V/20A, 220-240V/16A, (14) C13

AP6003A

	rv	

Lead time Usually in Stock

Main		
Main Input Voltage	230 V	
PDU Type	Basic	
Main Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V	
Input Connection Type	IEC 60320 C20	
Number of rack unit	OU	
Provided Equipment	Installation guide Safety guide	

# **Physical**

Color	Black
Height	20.59 in (52.3 cm)
Width	2.20 in (5.6 cm)
Depth	1.85 in (4.7 cm)
Net Weight	4.14 lb(US) (1.88 kg)
Mounting Location	Side
Mounting preference	Lower
Mounting Mode	Not rack-mountable
USB compatible	No
Mounting position	Vertical

## Input

Line Rated Current	16 A
Permissible voltage	100240 V
Max line current	20 A
Input current limits	20 A

Load Capacity	3300 VA
Input Frequency	50/60 Hz

## **Output**

Number of power socket outlets 14 IEC 60320 C13

#### Conformance

Product Certifications CUL Listed UL Listed

#### **Environmental**

Ambient Air Temperature for Operation	32122 °F (050 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5149 °F (-1565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.0015240.00 m)

# Ordering and shipping details

**GTIN** 731304327769

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.09 in (61.2 cm)
Package 1 Width	4.21 in (10.7 cm)
Package 1 Length	4.84 in (12.3 cm)
Package 1 Weight	5.62 lb(US) (2.55 kg)
SCC14	10731304327766

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## **Contractual warranty**

Warranty 2 years repair or replace

## Recommended replacement(s)