



Rack PDU, Basic, Zero U,14.4kW,208V,(24)C13,(4)C19, (2)L6-30R;3' Cord

AP7569

Ov	er	VI	e	W
----	----	----	---	---

Presentation	Basic Rack PDU 14.4 kW solution for high density installations
Lead time	Usually in Stock

Main

Walli	
Main Input Voltage	208 V 3 phase
PDU Type	Basic
Main Output Voltage	208 V 3 phase
Number of rack unit	OU
Cable length	3 ft (0.91 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets Toolless Mounting Kit

Physical

Color	Black
Height	70.00 in (177.8 cm)
Width	2.20 in (5.6 cm)
Depth	3.74 in (9.5 cm)
Net Weight	16.14 lb(US) (7.32 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Vertical

Input

Line Rated Current	40 A
Input current limits	50 A
Load Capacity	14400 VA
Input Frequency	50/60 Hz

Number of input connectors 1 CS8365

Output

2 NEMA L6-30R 24 IEC 60320 C13 Number of power socket outlets

4 IEC 60320 C19

Conformance

Product Certifications	cUL Listed CSA METI Denan UL Listed	
Standards	UL 60950	

Environmental

Ambient Air Temperature for Operation	23113 °F (-545 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.0015240.00 m)

Ordering and shipping details

GTIN 731304240754

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.98 in (205.7 cm)
Package 1 Width	12.24 in (31.1 cm)
Package 1 Length	3.11 in (7.9 cm)
Package 1 Weight	24.87 lb(US) (11.28 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)