



# APC Dry Contact I/O SmartSlot Card

AP9613

O				

Presentation	UPS management SmartSlot Card with Dry Contact (relay) support to monitor external triggers and initiate actions on external devices.
Lead time	Usually in Stock

#### Main

Number of rack unit	OU
Provided Equipment	User Manual USB cable

### **Physical**

Color	Black
Height	1.50 in (3.8 cm)
Width	4.76 in (12.1 cm)
Depth	4.49 in (11.4 cm)
Net Weight	0.46 lb(US) (0.21 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

### Conformance

Standards	EN 55022 Class A	
	EN 55024	
	EN 61000-3-2	
	EN 61000-3-3	
	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-6	
	FCC Part 15 class A	

## **Environmental**

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5149 °F (-1565 °C)
Storage Relative Humidity	095 %

# Ordering and shipping details

Category	09305 - INDUSTRIAL UPS
GTIN	731304293842
Returnability	No
Country of origin	РН

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.01 in (5.1 cm)
Package 1 Width	9.25 in (23.5 cm)
Package 1 Length	6.26 in (15.9 cm)
Package 1 Weight	0.88 lb(US) (0.4 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	7.01 lb(US) (3.181 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Lead free	Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	

## **Contractual warranty**

Warranty	2 years repair or replace	
----------	---------------------------	--

# Recommended replacement(s)