

Eaton 278755

Catalog Number: 278755

Eaton Moeller series xEffect - FAZ MCB. FAZ, 2-pole, tripping characteristic: C, rated current In: 8 A

General specifications

Product Name	Catalog Number
Eaton Moeller series xEffect - FAZ MCB	278755

Model Code	EAN
FAZ-C8/2	4015082787554

Product Length/Depth	Product Height
80 mm	75.5 mm

Product Width	Product Weight
36 mm	.222 kg

Compliances	Certifications
UL CSA09 (with supplementary protector only) RoHS conform	CSA (File No. 204453) UL (File No. E177451) UL 1077 UL (Category Control Number QVNU2, QVNU8) IEC/EN 60898 IEC/EN 60947-2 CSA (Class No. 3215-30) CE marking North America (UL recognized, CSA certified) CSA-C22.2 No. 235 EN45545-2 IEC 61373



Product specifications

Rated operational current for specified heat dissipation (In)

8 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Voltage rating (IEC/EN 60898-1)

415 VAC

10.4 Clearances and creepage distances

Meets the product standard's requirements.

Rated short-circuit breaking capacity (EN 60898) at 230 V

10 kA

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting Method

Top-hat rail IEC/EN 60715

Current limiting class

3

Rated short-circuit breaking capacity (EN 60898) at 400 V

10 kA

Amperage Rating

8 A

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity of screw terminals for main cable

10 mm² (2x)

Frequency rating - max

60 Hz

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.8 Connections for external conductors

Is the panel builder's responsibility.

Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

15 kA

Number of poles (total)

Resources

Certification reports

DA-DC-03_FAZ-B-C-D

Characteristic curve

[eaton-xeffect-faz-mcb-characteristic-curve.jpg](#)

[KL_FAZ_trip_B_C_D](#)

[122U023](#)

[122U026](#)

[eaton-mcb-xeffect-faz-characteristic-curve-002.eps](#)

[122U051](#)

[122U025](#)

[122U024](#)

[eaton-mcb-current-xeffect-faz-characteristic-curve.eps](#)

[eaton-mcb-tripping-characteristic-xeffect-faz-characteristic-curve-002.eps](#)

[eaton-mcb-xeffect-faz-characteristic-curve.eps](#)

[eaton-mcb-current-xeffect-faz-characteristic-curve-002.eps](#)

Drawings

[Mas_FAZ_2](#)

[1220DIM-55](#)

[eaton-mcb-xeffect-faz-dimensions-002.eps](#)

[eaton-xeffect-faz-mcb-dimensions-002.jpg](#)

[FAZ_idl_C_60947](#)

[FAZ_idl_C](#)

[eaton-mcb-faz-xeffect-faz-3d-drawing-002.eps](#)

[eaton-xeffect-faz-mcb-3d-drawing-010.jpg](#)

[122I084](#)

[FAZ_i2t_C](#)

[eaton-xeffect-faz-mcb-3d-drawing-009.jpg](#)

[eaton-xeffect-faz-mcb-3d-drawing-002.jpg](#)

eCAD model

[ETN.FAZ-C8_2](#)

Installation instructions

[IL019140ZU](#)

mCAD model

[DA-CS-faz_1pn_2p](#)

[DA-CD-faz_1pn_2p](#)

Specifications and datasheets

Terminal protection

Finger and hand touch safe, DGVV VS3, EN 50274

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

15 kA

Special features

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

Ambient operating temperature - max

75 °C

Heat dissipation per pole, current-dependent

0 W

Built-in depth

70.5 mm

Rated switching capacity (IEC/EN 60898-1)

10 kA

Features

Additional equipment possible

Lifespan, electrical

10000 operations

Rated switching capacity (IEC/EN 60947-2) at max voltage rating

10 kA

Connectable conductor cross section (solid-core) - min

1 mm²

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Number of poles

Two-pole

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

Selectivity class

3

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Wiring diagrams

[eaton-xpole-mm4-6-m-mcb-wiring-diagram-003.jpg](#)

122S101

[eaton-mcb-xeffect-faz-wiring-diagram-002.eps](#)

PLS_2P

Terminal capacity (control cable)

25 mm² (1x)

Used with

FAZ

Miniature circuit breaker

Mounting position

As required

Equipment heat dissipation, current-dependent

4.1 W

Tripping characteristic

C

Frequency rating - min

50 Hz

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Static heat dissipation, non-current-dependent

0 W

Application

Branch circuits, not as BCPD

Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Voltage type

AC

Number of poles (protected)

2

Frame

45 mm

Terminals (top and bottom)

Twin-purpose terminals

Heat dissipation capacity

0 W

Release characteristic

C

Width in number of modular spacings

2

Busbar material thickness

0.8 mm - 2 mm

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Enclosure width

80 mm

Voltage rating

240 V AC / 415 V AC

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Connectable conductor cross section (solid-core) - max

25 mm²

Degree of protection

IP40 (when fitted)

UL/CSA Type: -

IP20

IP20 (IEC)

Overvoltage category

III

Pollution degree

2

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Connectable conductor cross section (multi-wired) - min

1 mm²

Rated impulse withstand voltage (U_{imp})

4 kV

Operational voltage (IEC/EN 60947-2) - max

440 VAC

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Voltage rating at DC

60 V DC (per pole)

Admissible back-up fuse - max

125 A gL/gG

Voltage rating (UL)

480Y/277 V

Rated switching capacity (IEC/EN 60947-2)

15 kA

Voltage rating (UL CSA 13)

480 Y/277 V AC; 96 V DC

Connectable conductor cross section (multi-wired) - max

25 mm²

Mounting width per pole

17.5 mm

Type

FAZ

Miniature circuit breaker

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Operational switching capacity

7.5 kA

Breaking capacity

10 kA (UL1077)

Direction of incoming supply

As required

Rated operational voltage (Ue) - max

400 V

Rated service short-circuit breaking capacity (IEC/EN 60898-1)

7.5 kA

Mounting width

17.5 mm

Rated service short-circuit breaking capacity (IEC/EN 60947-2)

7.5 kA

Rated insulation voltage (Ui)

440 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)