

PRODUCT-DETAILS

E2.2 W FP I_u=2000 3p HR HR

E2.2 W FP I_u=2000 3p HR HR



General Information

Extended Product Type	E2.2 W FP I _u =2000 3p HR HR
Product ID	1SDA073909R1
EAN	8015644778422
Catalog Description	E2.2 W FP I _u =2000 3p HR HR
Long Description	FIXED PART WITHDRAWABLE FOR C.BREAKER SACE EMAX2 E2.2 2000 THREE-POLE WITH REAR HORIZONTAL TERMINALS

Ordering

Order Code US and Canada	Z2C20A0XX
EAN	8015644778422
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Width	317 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	36 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	570 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	41 kg
Package Level 1 EAN	8015644778422

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
Toxic Substances Control Act - TSCA	9AKK108467A8326

Additional Information

Current Type	AC
Electrical Durability	2000 cycle
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Product Main Type	SACE Emax 2
Product Name	Fixed Part
Product Type	Fixed Part
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC 800 V AC 900 V AC
Rated Uninterrupted Current (I_U)	2000 A
Recommended Screw Driver	Main Circuit M12
Standards	IEC
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m
Version	W FP

Certificates and Declarations (Document Number)

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity	9AKK106713A5902

- CE

Environmental Information	9AKK108467A6707
Instructions and Manuals	1SDH001000R0820
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
UL Certificate	No certification needed
VDE Certificate	No certification needed

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC002043 - Chassis part power circuit breaker
ETIM 7	EC002043 - Chassis part power circuit breaker
ETIM 8	EC002043 - Chassis part power circuit breaker
Object Classification Code	Q
UNSPSC	39122221
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370422
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

