

Eaton CH143DIU

Catalog Number: CH143DIU

Eaton's Bussmann series 3-Pole modular fuse holder, rated at 690 V a.c./750 V d.c. (IEC), 700 V a.c. (UL), 50 Amps (IEC and UL), fitted with a neon indicator, suitable for 14 x 51 mm Cylindrical fuses

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse holder	CH143DIU
	UPC
	051712685177
EAN	Product Length/Depth
5027590496810	76 mm
Product Height	Product Width
92 mm	80 mm
Product Weight	Compliances
263 g	CE Marked RoHS Compliant
Certifications	
IEC 60269-2 EAC IEC 60269-1 UL Listed File E14853	



Product specifications

Optical defect indication

Yes

Built-in depth

51.5 mm

Voltage rating at DC

750 V d.c. (IEC)

Material

Polyester

Lockable

Yes

Mounting method

DIN rail

2 x M4 Panel mounting screws

Operating temperature details

-20°C to +70°C

Amperage Rating

50 A

Voltage rating at AC

690 V a.c. (IEC) and 700 V a.c. (UL)

Number of Poles

Three-pole

Fuse type

C14G

C14M

Accessories

JV-L Multipole connector kit, CH14-CTP IP20 Protection accessory

Type

fuse accessory

Width in number of modular spacings

4.5

Fitted with:

Neon indicator

Used with

C14G, C14M, FW-A14F fuses

Fuse size

Resources

Catalogs

Product overview for machinery

Compliance information

UKCA Modular fuse-holders

CE Modular fuse-holders

Technical data sheets

10080 14 x 51 mm Modular fuse holder

720147 10 x 38 mm Modular fuse holder

10115 22 x 58 mm Modular fuse holder

14 x 51 mm

Model

CH14

Voltage rating

690 V

Application

Industrial and Commercial applications

Torque rating

Max 3.5 Nm

Concurrently switching N-neutral

No

Degree of protection

IP20



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)