Eaton FWP-900A

Catalog Number: FWP-900A

Eaton Bussmann series FWP high speed fuse, 250 Vac/dc, 900A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud

General specifications

Product Name

Catalog Number

Eaton Bussmann series high speed

FWP-900A

cylindrical fuse

UPC

051712795739

EAN

Product Length/Depth

5027590021890

193 mm

Product Height

Product Width

89 mm

89 mm

Product Weight

Warranty

3064 g

Not Applicable

Compliances

Certifications

CE Marked RoHS Compliant

UL Recognized CSA Certified



Product specifications Rated voltage DC 700 V Interrupt rating 200 kAIC Vac 50 kAIC at 700 Vdc 200 kAIC Center-to-center distance of connections 151.61 mm Insulated metal gripping lugs (IMGL) No Current type AC/DC Mounting method Stud Amperage Rating 8 A Fuse type FWP-A Fuse system (according to IEC 60269) Other Rated switching capacity 200 A Voltage rating 700 V (UL) Fuse indicator Non Indicating Construction size Other Clearing (I2T) 530000 at 700 V Rated voltage AC 700 V

Color None

Connection

Blade end x blade end

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - FWP-900A

Technical data sheets

FWP NA bolted fuse-links

Mounting dimension

Other

Utilization category

aR (accompanied semiconductor protection)

Watt losses

150 W

Type

High speed fuse

Fuse shape

Center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

91500

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia