

# Product data sheet

Specifications



## Rack PDU, Basic, 0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19

AP6120A

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 100 V  
120 V  
200 V  
208 V  
230 V  
240 V

PDU type Basic

Main Output Voltage 100 V  
120 V  
200 V  
208 V  
230 V  
240 V

Input Connection Type IEC 60320 C20

Number of rack unit 1U

Provided equipment Installation guide  
Safety guide

### Physical

Height 4.4 cm

Width 38.8 cm

Depth 9.3 cm

Net weight 1.56 kg

Mounting location Front  
Rear

Mounting preference No preference

Mounting mode Not rack-mountable

USB compatible No

Mounting position Horizontal

### Input

[In] rated current 16 A

Permissible voltage 100...240 V

Max line current	20 A
Input current limits	20 A
Load capacity	2300 VA
Network frequency	50/60 Hz

## Output

Number of power socket outlets	7 IEC 60320 C13 2 IEC 60320 C19
--------------------------------	------------------------------------

## Conformance

Product certifications	cUL listed CE EAC IRAM PSE UL listed VDE
------------------------	--

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21 cm
Package 1 Width	7.6 cm
Package 1 Length	43.6 cm
Package 1 Weight	2.02 kg
SCC14	50731304327856

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)