

# Product data sheet

Specifications



## Rack PDU 2G, Switched, ZeroU, 20A, 100-120V, (24) 5-20R

AP8930

**Product availability : Stock - Normally stocked in distribution facility**

### Overview

#### Presentation

APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

**Lead time** Usually in Stock

### Main

**Main Input Voltage** 120 V

**PDU Type** Switched

**Main Output Voltage** 120 V

**Input Connection Type** NEMA L5-20P

**Number of rack unit** 0U

**Cable length** 9.84 ft (3.00 m)

**Number of cables** 1

**Provided Equipment** Installation guide  
Rack Mounting brackets  
Serial configuration cable  
Safety guide

### Physical

**Color** Black

**Height** 70.51 in (179.1 cm)

**Width** 2.17 in (5.5 cm)

**Depth** 1.81 in (4.6 cm)

**Net Weight** 14.37 lb(US) (6.52 kg)

**Mounting Location** Side

**Mounting preference** No preference

**Mounting Mode** Not rack-mountable

**Mounting position** Vertical

## Input

Line Rated Current	16 A
Permissible voltage	100...120 V
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz

## Output

Number of power socket outlets	24 NEMA 5-20R
--------------------------------	---------------

## Conformance

Product Certifications	cUL Listed UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950-1

## Environmental

Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304307518
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.98 in (200.6 cm)
Package 1 Width	4.26 in (10.83 cm)
Package 1 Length	6.48 in (16.47 cm)
Package 1 Weight	18.96 lb(US) (8.6 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes

<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Recommended replacement(s)