

Product Selection

Red Body Switches

Type	Contact			Actuator Type	Cat. No.					
	Safety	Auxiliary	Action		Conduit		Connector§			
					M20	1/2 in NPT	12-Pin M23	8-Pin Micro (M12)*	Connect to ArmorBlock Guard I/O 5-Pin Micro (M12)*	
MT-GD2	3 N.C.	1 N.O.	BBM	—	440K-MT55002	440K-MT55085	440K-MT55094	—	—	
				GD2 Standard	440K-MT55074	440K-MT55022	440K-MT55095	—	—	
				Fully Flexible	440K-MT55075	440K-MT55029	440K-MT55096	—	—	
			MBB	—	440K-MT55004	440K-MT55088	440K-MT55100	—	—	
	2 N.C.	2 N.O.	BBM	—	440K-MT55005	440K-MT55086	440K-MT55097	440K-M21BNDH	—	
				GD2 Standard	440K-MT55076	440K-MT55026	440K-MT55098	—	—	
				Fully Flexible	440K-MT55077	440K-MT55087	440K-MT55099	—	—	
			MBB	—	440K-MT55006	440K-MT55089	440K-MT55101	—	—	
			Snap Acting	—	—	440K-M22ANDT	440K-M22ANDL	440K-M21ANDH	440K-M2NNNDS	—
				Extended Flat	440K-M22AEDM	440K-M22AEDT	—	—	—	—
				GD2 Standard	440K-M22ASDM	440K-M22ASDT	—	—	—	—
				Fully Flexible	440K-M22ABDM	440K-M22ABDT	—	—	—	—
MT-GD2 Latch Release	3 N.C.	1 N.O.	BBM	—	440K-MT55039	440K-MT55062	440K-MT55042	—	—	
				GD2 Standard	440K-MT55078	440K-MT55041	440K-MT55070	—	—	
				Fully Flexible	440K-MT55079	440K-MT55045	440K-MT55103	—	—	
			MBB	—	440K-MT55082	440K-MT55091	440K-MT55106	—	—	
	2 N.C.	2 N.O.	BBM	—	440K-MT55063	440K-MT55065	440K-MT55066	440K-M21BNDH-N5	440K-M2NNNDS-N5	
				GD2 Standard	440K-MT55080	440K-MT55050	440K-MT55104	—	—	
				Fully Flexible	440K-MT55081	440K-MT55051	440K-MT55052	—	—	
			MBB	—	440K-MT55083	440K-MT55092	440K-MT55105	440K-M21MNDH-N5	—	

§ For connector ratings see page 3-9.

* With a 5-pin micro (M12) connector, not all contacts are connected. See *Typical Wiring Diagram* on page 3-32 for wiring details.

⊛ With an 8-pin micro (M12) connector, not all contacts are connected. See *Typical Wiring Diagram* on page 3-32 for wiring details.

Yellow Body Switches

Type	Contact			Actuator Type	Cat. No.		
	Safety	Auxiliary	Action		Conduit	Connector§	
					1/2 in NPT	12-Pin M23	5-Pin Micro (M12)*
MT-GD2	2 N.C.	2 N.O.	Snap Acting	—	440K-M22ANYT	—	—
				Extended Flat	440K-M22AEYT	440K-M22AEYL	440K-M2NAEYS
—	2 N.C.	2 N.O.	MBB	—	440K-M22MNYT-N5	—	440K-M2NNNYS-N5

§ For connector ratings see page 3-9.

* With a 5-pin micro (M12) connector, not all contacts are connected. See *Typical Wiring Diagram* on page 3-32 for wiring details.

⊛ With an 8-pin micro (M12) connector, not all contacts are connected. See *Typical Wiring Diagram* on page 3-32 for wiring details.

3-Interlock Switches