

## DATA SHEET

# ARUBA 7000 SERIES MOBILITY CONTROLLERS

Improved network performance, visibility, and control

Aruba 7000 Series Mobility Controllers enhance WLAN performance by centralizing all control functionality for individual Aruba access points (APs) to improve AP utilization, security, and client roaming. Ideally suited for midsize campuses and branches, the 7000 Series can be deployed using Zero Touch Provisioning to simplify deployment.

## SIMPLE AND SECURE ACCESS

The 7000 Series serves a key role in [Dynamic Segmentation](#), providing Aruba's Policy Enforcement Firewall (PEF) to enforce policies based on user role, device type, application, and network location - and simplifying and securing wired and wireless network access. Traffic is encapsulated in GRE tunnels for complete encryption all the way from an AP or switch. This feature can be enabled with the ArubaOS PEF license and eliminates the need to manually configure SSIDs, VLANs or ACLs for each new client on the network.

## HIGH PERFORMANCE AND RELIABILITY

Each 7000 Series provides connectivity for up to 4,096 concurrent users or client devices, 64 access points and include multiple fiber WAN uplinks. With 8Gbps of maximum throughput to perform [Policy Enforcement Firewall \(PEF\)](#) features, the 7000 Series delivers plenty of horsepower for the most demanding enterprise environments.

For enhanced resiliency and availability, the 7000 Series can be clustered together in a network.

## 24/7 MISSION-CRITICAL NETWORKING

Aruba's unique patented wireless technologies are based on AI-powered machine learning algorithms and integrated directly into ArubaOS. Adaptive Radio Management, AirMatch and ClientMatch provide RF optimization techniques to improve user experience and network health based on changing environmental conditions, correct for noisy or congested RF and resolve sticky client issues during



\*7010 and 7030 Mobility Controllers shown

## KEY FEATURES

- Support for new Wi-Fi 6/6E (802.11ax), WPA3 and Enhanced Open – and existing standards
- Patented ClientMatch technology can now group together Wi-Fi 6 capable devices
- Dynamic Segmentation enforces wired and wireless access policies to simplify and secure the network
- Application awareness for 3,000+ applications without additional hardware
- Built-in AI-powered wireless/RF optimization
- 8 Gbps of maximum firewall throughput

user roaming. RFPProtect provides advanced spectrum analysis and wireless intrusion protection (WIPS/WIDS) to help identify and mitigate Wi-Fi and non-Wi-Fi sources of interference, as well as containment of potential security risks.

When deployed with Aruba Mobility Conductor, the 7000 Series can be joined to a controller cluster to increase scale, improve reliability using High Availability (HA), adopt configurations seamlessly based on hierarchy, support Live Upgrades to reduce maintenance windows, and share licenses from a global licensing pool.

Learn more about the 7000 Series Mobility Controller features in the [ArubaOS datasheet](#).



## SD-WAN DEPLOYMENT

For organizations that are now managing multiple WAN connections, the 7000 Series can be connected to Aruba's SD-WAN fabric right out of the box. SD-Branch is a rich WAN management solutions that is used to simplify management of traffic entering and exiting branch sites. Please refer to the [SD-Branch datasheet](#) for more information.

## MICROSOFT FEATURES

Aruba's integration with Microsoft enables unique application intelligence that detects Microsoft 365 and Teams traffic and then prioritizes them over less critical applications. IT can visualize call quality metrics such as MOS, latency, jitter, and packet loss for additional insights.

## ENHANCED CAPABILITIES

### Client optimization

The Wi-Fi 6 and Wi-Fi 6E standard brings enhanced performance, speed, and efficiency with key features such as OFDMA and bidirectional MU-MIMO. Combined with Aruba's patented ClientMatch technology, 802.11ax clients will now be grouped together to optimize the multi-user experience.

### Enhanced wireless security

Support for WPA3 brings stronger encryption and authentication methods, while Enhanced Open brings automatic security to open networks. The new WPA2-MPSK feature enables simpler passkey management for WPA2 devices – should the Wi-Fi password on one device need to be changed, no additional key changes are needed for other devices on the network.

### Dynamic Segmentation

To simplify and better secure wired and wireless network access, the 7000 Series can enforce per-user and device roles across wired and wireless networks by integrating with ClearPass Policy Manager or using Aruba Central NetConductor. This ensures consistent policy regardless of user role and device type, and eliminates the need to configure unnecessary SSIDs, ACLs, VLANs and subnets at every node in the network.

### Policy Enforcement Firewall

Wired and wireless user and application traffic can be tunneled to a stateful firewall on the 7000 Series through GRE tunnels for inspection as part of the PEF

add-on license. Policies are then enforced based on user role, device type, application and location as described in Dynamic Segmentation.

### Application visibility and control

As part of the PEF, Deep Packet Inspection (DPI) provides application visibility to evaluate and optimize performance and Quality of Service policies for over 3,000 applications - even for encrypted or hidden traffic.

### Web content filtering

WebCC is an add-on feature that classifies websites by content category and rates them by reputation. It can also block, apply QoS, bandwidth-limit, mirror, and log web content.

### Unified Communications and Collaboration (UCC)

Visualize and troubleshoot networks based on call quality metrics such as MOS, latency, jitter and packet loss. Supported applications include: Teams, Skype for Business®, Wi-Fi Calling, Facetime, SIP, Jabber, Spark and more.

### Zero Touch Provisioning

The 7000 Series can be factory-shipped and deployed onsite with cloud-based Aruba Activate. For network-specific requirements, settings can be applied based on hierarchical configuration.

### Integrated VPN services

With support for IPSec/SSL VPNs, Aruba remote APs (RAPs) and Aruba VIA VPN users can establish encrypted sessions without any additional hardware required.

### Third-party security integration

For advanced malware or antivirus protection, the 7000 Series can assume the role of an on-premises agent of centrally-hosted firewalls such as those provided by Palo Alto Networks and Check Point Software. Dedicated firewall appliances are no longer needed at each branch.

## AOS 10 CONSIDERATIONS

When deploying the 7000 Series using AOS 10 and Aruba Central, many enhanced capabilities (Policy Enforcement Firewall, WebCC, and UCC) reside as services within the Central cloud and are included in the Central subscription license. Refer to the [Aruba Central](#) data sheet for more details on what is included in the license.



## PERFORMANCE AND CAPACITY

Features	7010	7030
Maximum campus or remote AP licenses	32	64
Maximum concurrent users/devices	2,048	4,096
Maximum VLANs	4,096	4,096
Active firewall sessions	64K	64K
Concurrent GRE tunnels	512	1,024
Concurrent IPsec sessions	2,048	4,096
Concurrent SSL sessions	2,048	4,096
Firewall throughput (Gbps)	8	8
Wired Bridged Throughput (Gbps)	8	8
Encrypted throughput 3DES (Gbps)	2.4	2.4
Encrypted throughput AES-CBC-256 (Gbps)	2.6	2.6
Encrypted throughput AES-CCM (Gbps)	3.4	4.0
Encrypted throughput AES-GCM-256 (Gbps)	3.3	3.4

## INTERFACES AND INDICATORS

Features	7010	7030
Form factor/footprint	1xRU	1xRU
10/100/1000BASE-T	16	8 (combo)
1000BASE-X	2xSFP	
10G Ports (10G or 1G supported)	-	-
USB 2.0	2	1
Management/status LEDs	Yes	Yes
LINK/ACT and status LEDs	Yes	Yes
LCD panel and navigation buttons	Yes	Yes
Console port	mini USB, RJ-45	mini USB, RJ-45
Out-of-band management port	Yes	No

## POWER OVER ETHERNET (PoE) SUPPORT

	7010	7030
PoE <sup>1</sup> Role/Mode	Power Source Equipment (PSE)	-
PoE In or Out	Out	-
Max concurrent of PoE Ports	12	-
Max <sup>2</sup> concurrent PoE+ Ports	12	-
PoE Power Budget	150W	-

<sup>1</sup> PoE: 802.3af, up to 15.4W from the PSE and up to 12.95W at the PD, not to exceed the total PoE Power Budget.

<sup>2</sup> PoE+: 802.3at, up to 30W per port from the PSE and up to 25.5W at the PD, not to exceed the total PoE Power Budget.



PHYSICAL		
	7010	7030
Dimensions (H x W x D)	4.42 cm x 31.75 cm x 33.7 cm (1.74" x 12.75" x 13.3")	4.4 cm x 30.5 cm x 21.1 cm (1.7" x 12" x 8.3")
Weight	3.4 kg (7.5 lbs)	2.06 kg (4.54 lbs)
MTBF (hours, @ 40C)	232,843	390,679

ENVIRONMENTAL RANGE		
Specification	7010	7030
Operating temperature	0° C to 40° C	
Storage temperature	-40° C to 70° C	
Humidity/Storage Humidity	5% to 95%, NC	5% to 95%, NC
Operating Altitude	10,000 feet	
Acoustic noise <sup>3</sup>	39.8 – 58.6 dBA	29.1 – 57.4 dBA
Maximum Heat Dissipation (BTU/hour)	300	168
Maximum power consumption	190W (with PoE)	55W
Power Source	internal power supply	internal power supply

<sup>3</sup> Sound power per ETSI 300 753 in accordance with ISO 7779

POWER ADAPTER AND SUPPLY SPECIFICATIONS		
Features	12v - 30W	150-watt
Input voltage range	90 VAC to 264 VAC	90 VAC to 264 VAC
Output Voltage	+12VDC, 4A	54VDC, 2.78A
Input frequency	47-63 Hz	47-63 Hz
AC line input current (steady state)	1.0A	2.0A
Operating Temperature	-0o to +40o C	-0o to +40o C
Cooling	-	-
Weight	.24 kg (.53 lbs)	.72 kg (1.58 lbs)



REGULATORY AND SAFETY COMPLIANCE		
Features	7010	7030
Regulatory SKU information	ARCNO103	ARCN7030
Minimum ArubaOS Release	8.x	8.x
	WI-FI CERTIFIED WPA3, AOS 8.4; WI-FI CERTIFIED Enhanced Open, AOS 8.4; Wi-Fi 6 (802.11ax), AOS 8.4; WI-FI CERTIFIED 802.11ad, AOS 8.4	
Safety certifications	UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition EN 60950:2005 IEC 60950-1 Second Edition NOM (obtained by partners and distributors)	
Electromagnetic emissions certifications	FCC Part 15 Class B CE AS/NZS CISPR22 Class B CISPR22 Class A (7010, 7024, 7030), Class B (7005) EN55022 Class A (7010, 7024, 7030), Class B (7005) ICES-003 Class A (7010, 7024, 7030), Class B (7005) VCCI Class A (7010, 7024, 7030), Class B (7005) EN61000-3-2 EN61000-3-3 EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11, AS/NZS 3548 KN22 Class B KCC CNS13438 Class B EN55024/CISPR24 KN24 Industry Canada Class B CE mark, cTUVus, CB, C-tick, Anatel, NOM, MIC	
Telco	Common Language Equipment Identifier (CLEI) Code	

### SERVICE AND WARRANTY INFORMATION

- Hardware: 1 year parts/labor, can be extended with support contract
- Software: 90 days, can be extended with support contract



ORDERING INFORMATION	
Part Number	Description
<b>Aruba 7010 Series Mobility Controllers</b>	
JW678A	Aruba 7010 (RW) 16p 150W PoE+ 10/100/1000BASE-T 1G BASE-X SFP 32 AP and 2K Clients Controller
JW679A	Aruba 7010 (US) 16p 150W PoE+ 10/100/1000BASE-T 1G BASE-X SFP 32 AP and 2K Clients Controller
JW680A	Aruba 7010(IL) 16p 150W PoE+ 10/100/1000BASE-T 1G BASE-X SFP 32 for AP and 2K Clients Controller
JW681A	Aruba 7010 (JP) 16p 150W PoE+ 10/100/1000BASE-T 1G BASE-X SFP for 32 AP and 2K Clients Controller
JW702A	Aruba 7010 (RW) FIPS/TAA 16p 150W PoE+ 10/100/1000BASE-T 1GBASE-X SFP 32 AP and 2K Clients Controller
JW703A	Aruba 7010 (US) FIPS/TAA 16p 150W PoE+ 10/100/1000BASE-T 1GBASE-X SFP 32 AP and 2K Clients Controller
JW704A	Aruba 7010 (IL) FIPS/TAA 16p 150W PoE+ 10/100/1000BASE-T 1G BASE-X SFP 32 AP and 2K Clients Controller
JW705A	Aruba 7010 (JP) FIPS/TAA 16p 150W PoE+ 10/100/1000BASE-T 1GBASE-X SFP 32 AP and 2K Clients Controller
JY850A	Aruba 7010 (EG) 16x 1000BASE-T + 2x SFP Ports 32 AP Branch Controller

ORDERING INFORMATION	
Part Number	Description
<b>Aruba 7030 Series Mobility Controllers</b>	
JW686A	Aruba 7030 (RW) 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JW687A	Aruba 7030 (US) 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JW688A	Aruba 7030 (IL) 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JW689A	Aruba 7030 (JP) 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JW710A	Aruba 7030 (RW) FIPS/TAA 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JW711A	Aruba 7030 (US) FIPS/TAA 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JW712A	Aruba 7030 (IL) FIPS/TAA 8p Dual Pers 10/100/1000BASE-T 1GBASE-X SFP 64 AP and 4K Clients Controller
JW713A	Aruba 7030 (JP) FIPS/TAA 8p Dual Pers 10/100/1000BASE-T/1GBASE-X SFP 64 AP and 4K Clients Controller
JY851A	Aruba 7030 (EG) 8x 1000BASE-T or 8xSFP64 AP Branch Controller
<b>Controller Accessories</b>	
JX989A	AP-AC-12V30A 12V 30W Power Adapter
JX933A	Aruba PSU-150-AC 150W AC Power Supply
JW083A	Aruba SPR-WL2-MNT S2500/S1500 7024 Wall and Rack Mount Kit
JW084A	Aruba 7005-MNT-19 7005 Series 19-inch Rack Mount Kit
JX934A	Aruba 7008-MNT-19 7008 Series 19-inch Rack Mount Kit
JW085A	Aruba 7010-MNT-19 7010 Series Replacement 19-inch Rack Mounting Kit
JW082A	Aruba SPR-RK3-MNT 7205/7024/S2500-xx/S1500-24P/48P Spare Front Rack Mount
JW086A	Aruba 7030-MNT-19 7030 Series Replacement 19-inch Rack Mounting Kit



ORDERING INFORMATION			
Part Number	Description	7010	7030
<b>Transceivers</b>			
JW087A	Aruba 1000BASE-LX LC Connector SFP XCVR	X	X
JW088A	Aruba 1000BASE-SX LC Connector SFP XCVR	X	X
JW089A	Aruba 1000BASE-T RJ45 Connector SFP XCVR	X	X
JW149A	SFP-EX 1000BASE-EX LC SFP XCVR	X	X
JW150A	SFP-ZX 1000BASE-ZX LC SFP XCVR	X	X
J4859D	Aruba 1G SFP LC LX 10km SMF Transceiver	X <sup>1</sup>	X <sup>1</sup>
J4858D	Aruba 1G SFP LC SX 500m OM2 MCRF Transceiver	X <sup>1</sup>	X <sup>1</sup>
J4860D	Aruba 1G SFP LC LH 70km SMF Transceiver	X <sup>2</sup>	X <sup>2</sup>
J8177D	Aruba 1G SFP RJ45 T 100m Cat5e Transceiver	X <sup>1</sup>	X <sup>1</sup>
JL745A	Aruba 1G SFP LC SX 500m MMF TAA XCVR	X <sup>3</sup>	X <sup>3</sup>
JL746A	Aruba 1G SFP LC LX 10km SMF TAA XCVR	X <sup>3</sup>	X <sup>3</sup>
JL747A	Aruba 1G SFP RJ45 T 100m Cat5e TAA XCVR	X <sup>3</sup>	X <sup>3</sup>
JL748A	Aruba 10G SFP+ LC SR 300m MMF TAA XCVR	X <sup>3</sup>	X <sup>3</sup>
JL749A	Aruba 10G SFP+ LC LR 10km SMF TAA XCVR	X <sup>3</sup>	X <sup>3</sup>

### ACCESSORIES FOR 7005 AND 7008 CONTROLLERS

Accessories for 7005 and 7008 Controllers are orderable although the controllers themselves are end of sale.

7005 ACCESSORIES	
Power Cord Part Number	Description
JX989A	AP-AC-12V30A 12V/30W AC/DC Desktop Style 1.7/4.0/9.5mm Circular 90 Deg Plug DoE Level VI Adapter
R3J99A	12V/36W AC/DC power adapter type A
Rack Mount Part Number	Description
JW084A	Aruba 7005-MNT-19 7005 Series 19-inch Rack Mount Kit

7008 ACCESSORIES	
Power Cord Part Number	Description
JW113A	PC-AC-ARG Argentina 220V AC 10A 2-meter AC Power Cord
JW114A	PC-AC-AUS Australian AC Power Cord
JW115A	PC-AC-BR Brazil AC Power Cord
JW116A	PC-AC-CHN China AC Power Cord
JW117A	PC-AC-DEN Denmark 220V AC 10A 2-meter AC Power Cord
JW118A	PC-AC-EC Continental European/Schuko AC Power Cord
JW119A	PC-AC-IN India AC Power Cord
JW120A	PC-AC-IL Israel 250V AC 10A 2-meter AC Power Cord
JW121A	PC-AC-IT Italian AC Power Cord
JW122A	PC-AC-JP Japanese AC Power Cord
JW123A	PC-AC-KOR Korea AC Power Cord



7008 ACCESSORIES	
Power Cord Part Number	Description
JW124A	PC-AC-NA North America AC Power Cord
JW125A	PC-AC-SWI Switzerland 220V AC 10A 2-meter AC Power Cord
JW127A	PC-AC-UK UK AC Power Cord
JW128A	PC-AC-ZA South Africa 250V AC 10A 2-meter AC Power Cord
Rack Mount Kit Part Number	Description
JX934A	Aruba 7008-MNT-19 7008 Series 19-inch Rack Mount Kit

For additional information on the Aruba 7000 Series Mobility Controllers please refer to:

- [ArubaOS Network Operating System Data Sheet](#)
- [7000 Series Mobility Controller](#)
- [7000 Series Ordering Guide](#)
- [SD-Branch Data Sheet](#)