



Dry-Shrink™ HSTT75-YK1 Heat Shrink

HSTT75-YK1

Thin wall heat shrink in 6" pieces, multi-color, single diameter, .75" (19.0mm) diameter, cross-linked polyolefin.

Specifications

Product Type	Heat Shrink
Adhesive Lined	No
Color	Assorted
Material	Flame retardant polyolefin cross-linked except clear
Maximum Operating Temperature (°C)	135
Maximum Operating Temperature (°F)	275
Minimum Operating Temperature (°C)	-55
Minimum Operating Temperature (°F)	-67
Nominal Diameter (In.)	0.75
Nominal Diameter (mm)	19.1
Nominal Recovered Wall Thickness (In.)	0.03
Nominal Recovered Wall Thickness (mm)	0.8
Sub Brand	Dry-Shrink™
Overall Length (In.)	6
Overall Length (ft.)	0.5
Overall Length (m)	0.1524
Overall Length (mm)	152.4
Standards Met	UL Recognized, CSA Approved, MIL SPEC
Shrink Ratio	2:1
Shrink Temperature (°C)	90
Shrink Temperature (°F)	194
Maximum Recovered Inside Diameter (In.)	0.375
Maximum Recovered Inside Diameter (mm)	9.5
Minimum Expanded Inside Diameter (In.)	0.75
Minimum Expanded Inside Diameter (mm)	19.1
Application	For Dry Locations

Packaging Detail

UPC	07498390767
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0245
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.2446